

The `latex-lab-floats` package

Tagging of floats

L^AT_EX Project*

v0.81p 2026-09-09

Abstract

The following code implements a first draft for the tagging of float environments

1 Introduction

The code here handles the tagging of float environments.

Figures (and tables) are in L^AT_EX typically typeset in float environments. These are boxes which can “float” away to special float areas on the pages, e.g., to the top or the bottom of a page or to special float pages. If the rules allow it they can also be placed in the main text stream (“here”). Floats can also be collected at the end of the document. In either case the order within each type of floats (e.g., figures, tables, algorithms, etc.) is preserved.

A special type, called a H-float, (provided by the float package) is always placed in the main text stream and does not necessarily preserve the order with normal floats of the same type: It is basically a minipage with a caption.

Floats typically contain a figure (or a table, etc.) and a caption, but more complex constructions with subfigures, copyright statements, sources or additional description are possible too.

In the L^AT_EX source a float is normally more or less at the place of the first call-out, but when preparing a document for print the code is sometimes moved around to place floats in a more visually pleasing way.

2 Tagging

Floats (with the exception of H-floats) do not belong into the text stream, they are “consultation objects”: Readers must be able to choose if and when they read the float. Floats can have captions: the PDF rules require that if a **Caption** structure element is used, it is the first or last structure in its parent structure. This poses some challenges on a good tagging.

In PDF 2.0 there is the suitable **Aside** tag which hopefully will be handled correctly regarding the reading order once processor actually support PDF 2.0. But in PDF 1.7 we rolemap it to **Note** and this doesn’t lead to a good reading order. The code therefore defers the output of float: it collects the float structures and moves them to a **Sect**

*Initial implementation done by Ulrike Fischer

structure which is flushed out at the end of the document or earlier if the author requests it. (H-floats once they are handled will not be moved).

To fulfill the requirement that a **Caption** should be at the begin or end, we always move it to the begin of the structure. If a float has two captions the author has to insert a command which splits the float in two.

Subfigures and subcaptions are currently not handled, but will be implemented as simple **Part** with their own **Caption**.

Unknown float types are put into a generic structure when they are encountered in the source. To add support for a new float type the **float/new** key described below can be used.

3 Links

`hyperref` doesn't patch the caption commands anymore if `\DocumentMetadata` is used. The code here has to add a target for links. To improve the linking behavior, it add this target at the begin of the float (and at the begin of split if the float is split) and changes `\caption` so that a link to a caption label will go to this target.

4 Keys

The code adds the following keys for the `\tagpdfsetup` command:

<code>float/new</code>	
<code>float/flush</code>	
<code>float/split</code>	
<code>float/container</code>	

float/new This sets up the needed code for a new float type. The value is the `<captype>` which should be the same name as the name stored in `\captype`. The code defines symbolic structure names `float/<captype>s` (for the container), `float/<captype>` (for a single float), `float/<captype>/caption` and `float/<captype>/label` (for the caption and its label) and assigns standard roles to them. The roles can be changed with `\AssignStructureRole`.

float/flush This will flush out all so far deferred floats (currently table and figure) into a container. The value is a sectioning level for which `\toclevel@<name>` exists, e.g., `section` or `chapter`, or an integer number describing the level, like 1 for the section level. The container will then behave like a sectioning command of this level and create a `Sect` structure element containing the floats. The default value is the current sectioning level. The command should typically be used directly before a sectioning of the same or higher level. E.g. this here is wrong as following text “some text” would no longer be inside subsection A:

```
\DocumentMetadata{tagging=on}
\documentclass{article}

\begin{document}
\section{section A}
\subsection{subsection A}
\begin{figure}
\caption{hallo}
\end{figure}
\tagpdfsetup{float/flush}
some text
\section{section B}
\end{document}
```

Correct would be to put it directly before `\subsection{section B}`. The key issues a `\par` to end the current paragraph.

The floats will then be inserted as a `Sect` of this level (all `Sect` of smaller or equal level are closed). The key then creates a new container for following floats. At the end of the document all remaining floats will be flushed automatically.

float/split This can be used inside a float if there are two captions. It will only work reasonably well if the content of the float parts are in a sensible order and can be separated by this command. More complex setups with tabulars will need more thoughts.

float/defer The value `false` disables the deferring of floats in a container: the float structure is then inserted directly where it appears in the source. The key sets a global boolean. It can be used in the document to switch the collection on and off. The default value is `true`.

float/here This is the inverse of the `defer` key and so a shorter way to disable the deferring. The default value is `true`.

5 Kernel commands

\@current@float@struct This variable holds the number of the current float structure. With tagging this is the structure number, without tagging a unique counter. A float can contain more than one float structure (e.g., if there is more than one caption).

\@makecaption \@makecaption is defined by the classes so we overwrite it for now at begin document.

```
1 <@=tag>
2 <*package>
```

6 Implementation

```
3 \ProvidesExplPackage {latex-lab-testphase-float} {\ltlabfloatdate} {\ltlabfloatversion}
4 {Code related to the tagging of floats}
```

6.1 Variables

We rolemap floats to Aside, and float sections to Sect.

\g__tag_float_sect_prop These variables will hold the structure number for the float container and the list of float types. Currently only figure and table are supported TODO: interface to declare new float types. To set the target for links we need also a unique counter. With tagging we could use the structure number, but the structure commands now are hidden inside tagging sockets so we use a dedicated counter.

```
5 \prop_new:N \g__tag_float_sect_prop
6 \seq_new:N \g__tag_float_types_seq
7 \seq_gput_right:Nn \g__tag_float_types_seq {figure}
8 \seq_gput_right:Nn \g__tag_float_types_seq {table}
9 \tl_new:N \@current@float@struct
10 \int_new:N \g__tag_float_int
```

(End of definition for \g__tag_float_sect_prop and others. This variable is documented on page 4.)

\g__tag_float_sect_bool With this boolean float collection is switched on and off. Currently it is always on and set globally. TODO: think if an interface is needed. TODO: would a local variable make more sense?

```
11 \bool_new:N \g__tag_float_sect_bool
12 \bool_gset_true:N \g__tag_float_sect_bool
```

(End of definition for \g__tag_float_sect_bool.)

\l__tag_float_tmpa_tl
\l__tag_float_tmpp_tl

```
13 \tl_new:N \l__tag_float_tmpa_tl
14 \tl_new:N \l__tag_float_tmpp_tl
```

(End of definition for \l__tag_float_tmpa_tl and \l__tag_float_tmpp_tl.)

`\_tag_float_init:` To be able to set unique targets for links, we need a counter outside the tagging sockets.
 TODO: check if this command should be public or a socket or a hook.

```

15 \cs_new_protected:Npn \_tag_float_init:
16 {
17   \int_gincr:N \g__tag_float_int
18   \tl_set:Nx \c_current@float@struct { \int_use:N \g__tag_float_int}
19 }

```

(End of definition for _tag_float_init:.)

6.2 Setup for a new float type

A new float type needs

- symbolic names for the float, the caption and the label
- symbolic name for the container
- and it must be recorded in the sequence.

This is all done with the following key. The value is the captype.

```

20 \msg_new:nnn { tag }{ float-exist }
21 {
22   Float~type~#1~is~already~setup~for~tagging.\
23   Ignoring~'float/new'~\msg_line_context:
24 }
25 \keys_define:nn {_tag/setup}
26 {
27   float/new .code:n =
28   {
29     \seq_if_in:NnTF \g__tag_float_types_seq {#1}
30     {
31       \msg_info:nnn { tag } { float-exist }{#1}
32     }
33     {
34       \NewStructureName{float/#1s}
35       \AssignStructureRole{float/#1s}{Sect}
36       \NewStructureName{float/#1}
37       \AssignStructureRole{float/#1}{float}
38       \NewStructureName{float/#1/caption}
39       \AssignStructureRole{float/#1/caption}{Caption}
40       \NewStructureName{float/#1/label}
41       \AssignStructureRole{float/#1/label}{Lbl}
42       \seq_gput_right:Nn \g__tag_float_types_seq {#1}
43     }
44   }
45 }

```

6.3 Moving float structures

Currently it is for all float types or none. Probably we will need some more options here to select some float types.

```

float/defer
float/here
46 \keys_define:nn{__tag/setup}
47 {
48   float/defer .bool_gset:N = \g__tag_float_sect_bool
49   ,float/here .bool_gset_inverse:N = \g__tag_float_sect_bool
50 }

```

(End of definition for float/defer and float/here. These functions are documented on page ??.)

```

\__tag_float_container_new:n This creates a new container and then stashes it.
51 \cs_new_protected:Npn \__tag_float_container_new:nN #1 #2 % #1 captype #2 tl-var to return nu
52 {
53   \tag_struct_begin:n{tag=\UseStructureName{float/#1s},stash}
54   \tag_get:nN {struct_num} #2
55   \prop_gput:Nne\g__tag_float_sect_prop {#1-struct}{#2}
56   \tag_struct_end:
57 }
58 \cs_generate_variant:Nn \__tag_float_container_new:nN {eN}

```

(End of definition for __tag_float_container_new:n.)

__tag_float_init_collect: This initializes a container structure for every float type. It can be used more than once in a document, this allows to have e.g. chapter wise containers.

```

59 \cs_new_protected:Npn \__tag_float_init_collect:
60 {
61   \bool_if:NT\g__tag_float_sect_bool
62   {
63     \seq_map_inline:Nn\g__tag_float_types_seq
64     {
65       \__tag_float_container_new:nN {##1}\l__tag_tmpa_tl
66     }
67   }
68 }

```

(End of definition for __tag_float_init_collect:.)

__tag_float_stop_sect: This pushes out the floats. For every type it checks if there is actually a float of this type and then writes out the container structure.

```

69 \cs_new_protected:Npn \__tag_float_stop_sect:
70 {
71   \seq_map_inline:Nn\g__tag_float_types_seq
72   {
73     \prop_get:NnNT\g__tag_float_sect_prop{##1-used}\l__tag_float_tmpa_tl
74     {
75       \prop_get:NnNF\g__tag_float_sect_prop{##1-struct}\l__tag_float_tmpb_tl
76       {
77         \__tag_float_container_new:eN {##1}\l__tag_float_tmpb_tl
78       }
79       \exp_args:Ne
80       \tag_struct_use_num:n{\l__tag_float_tmpb_tl}
81       \prop_gremove:Nn \g__tag_float_sect_prop{##1-used}
82     }
83   }
84 }

```

(End of definition for `\__tag_float_stop_sect:`)

flush/float This is a key for `\tagpdfsetup` to flush out the collected floats. The value allows to set to which level the create Sect belongs. So `section` will close all previous Sect until the section level and create a new section structure.

```

85 \keys_define:nn { __tag / setup }
86 {
87   float/flush .code:n =
88   {
89     \par
90     \cs_if_exist:cTF{toclevel@#1}
91     { \UseTaggingSocket{sec/end}{\int_eval:n{\use:c{toclevel@#1}}}}
92     { \UseTaggingSocket{sec/end}{\int_eval:n{#1}}}
93     \__tag_float_stop_sect:
94     \__tag_float_init_collect:
95   },
96   float/flush .default:n = \@currentseclevel
97 }

```

(End of definition for `flush/float`. This function is documented on page ??.)

flush-floats (deprecated) This is the same key for the deprecated command `\tagtool` to flush out the collected floats. Kept for compatibility for now but will be removed at some time. The value allows to set to which level the create Sect contains. So `section` will close all previous Sect until the section level and create a new section.

```

98 \keys_define:nn { tag / tool}
99 {
100   flush-floats .meta:nn = {\__tag/setup}{float/flush=#1},
101   flush-floats .default:n = \@currentseclevel
102 }

```

(End of definition for `flush-floats (deprecated)`. This function is documented on page ??.)

We need at least one pair

```

103 \AddToHook{begindocument/end}[latex-lab/float]
104 {\__tag_float_init_collect:}
105 \AddToHook{tagpdf/finish/before}[latex-lab/float]
106 {\par\__tag_sec_end:n{-10}\__tag_float_stop_sect:}
107 \DeclareHookRule{tagpdf/finish/before}[latex-lab/float]{before}{tagpdf}

```

6.4 Splitting floats

float/split TODO: check if the target affect spacing!!

```

108 \keys_define:nn { __tag / setup}
109 {
110   float/split .code:n =
111   {
112     \UseTaggingSocket{float/end}
113     \__tag_float_init:
114     \UseTaggingSocket{float/begin}
115     \MakeLinkTarget*{floatstructure.\@current@float@struct}
116   }
117 }

```

(End of definition for float/split. This function is documented on page 3.)

split-float (deprecated) This is the same key for the deprecated command `\tagtool` to split a float. Kept for compatibility for now but will be removed at some time.

```

118 \keys_define:nn { tag / tool}
119   {
120     split-float .meta:nn = {__tag/setup}{float/split}
121   }

```

(End of definition for split-float (deprecated). This function is documented on page ??.)

6.5 Tagging sockets

The tagging sockets are declared in `ltagging`. Currently we have the tagging sockets `float/hmode/begin`, `float/hmode/end`, `float/begin` and `float/end`. All sockets have no argument.

support/float/hmode/begin (plug) This plug should be used if a float is called in hmode. It then closes the MC-chunks and starts the structure.

```

122 \NewTaggingSocketPlug{float/hmode/begin}{kernel}
123   {
124     \__tag_float_stop_par:
125   }
126 \AssignTaggingSocketPlug{float/hmode/begin}{kernel}

```

support/float/hmode/end (plug) This plug should be used if a float is called in hmode; at the end of the float it then restarts the MC.

```

127 \NewTaggingSocketPlug{float/hmode/end}{kernel}
128   {
129     \__tag_float_start_par:
130   }
131 \AssignTaggingSocketPlug{float/hmode/end}{kernel}

```

(tagsupport/float/begin) (plug)

```

132 \NewTaggingSocketPlug{float/begin}{kernel}
133   {
134     \__tag_float_begin:
135   }
136 \AssignTaggingSocketPlug{float/begin}{kernel}

```

t (tagsupport/float/end) (plug)

```

137 \NewTaggingSocketPlug{float/end}{kernel}
138   {
139     \__tag_float_end:
140   }
141 \AssignTaggingSocketPlug{float/end}{kernel}

```

`\__tag_float_stop_par:` if a float is in a par, we need commands to stop and restart the P-mc

```

\__tag_float_start_par:
142 \cs_new_protected:Npn \__tag_float_stop_par:
143   {
144     \tag_mc_end:
145     \bool_if:NF \g__tag_float_sect_bool
146     {

```

```

147     \tag_struct_end:
148   }
149 }
150 \cs_new_protected:Npn \__tag_float_start_par:
151 {
152   \bool_if:NF \g__tag_float_sect_bool
153   {
154     \tag_struct_begin:n{tag=\UseStructureName{para/textblock}}}%
155   }
156   \tag_mc_begin:n{tag=P}
157 }

```

(End of definition for __tag_float_stop_par: and __tag_float_start_par:.)

These commands are the main commands to start and end the float tagging.

```

158 \cs_new_protected:Npn \__tag_float_begin:
159 {%

```

We test if the float structure should be included directly or move to a dedicated section.

```

160   \seq_if_in:NoTF \g__tag_float_types_seq{\@capttype}
161   {
162     \bool_if:NTF \g__tag_float_sect_bool
163     {
164       \prop_get:NoNF \g__tag_float_sect_prop{\@capttype-struct}\l__tag_float_tmpa_tl
165       {
166         \__tag_float_container_new:eN {\@capttype}\l__tag_float_tmpa_tl
167       }
168       \tag_struct_begin:e
169       {
170         tag=\UseStructureName{float/\@capttype},
171         parent=\l__tag_float_tmpa_tl
172       }%
173       \prop_gput:Nee \g__tag_float_sect_prop {\@capttype-used}{true}
174     }
175     {
176       \tag_struct_begin:n{tag=\UseStructureName{float/\@capttype}}
177     }
178   }
179   {
180     \tag_struct_begin:n{tag=\UseStructureName{float/generic}}
181   }
182   \tl_set:N\@current@float@struct{\tag_get:n{struct_num}}}%
183   \typeout{Float structure: \@current@float@struct}
184 }
185
186 \cs_new_protected:Npn \__tag_float_end:{\tag_struct_end:} %end Aside
187

```

6.6 Patching

This patches the main command `\xfloat`. There is a `:` in the code, so we disable `expl3` syntax

```

188 \ExplSyntaxOff

```

```

189 \def\@xfloat #1[#2]{%
190   \@nodocument
191   \def \@cuptype {#1}%
192   \def \@fps {#2}%
193   \@onelevel@sanitize \@fps
194   \def \reserved@b {!}%
195   \ifx \reserved@b \@fps
196     \@fpsadddefault
197   \else
198     \ifx \@fps \@empty
199       \@fpsadddefault
200     \fi
201   \fi
202   \ifhmode
203     \@bsphack

```

If the float is in hmode we have to interrupt the P

```

204   \UseTaggingSocket{float/hmode/begin}%
205   \@floatpenalty -\@Mii
206   \else
207     \@floatpenalty-\@Miii
208   \fi
209   \ifinner
210     \@parmoderr\@floatpenalty\z@
211   \else
212     \@next\@currbox\@freelist
213     {%
214       \@tempcnta \sixt@@n
215       \expandafter \@tfor \expandafter \reserved@a
216       \expandafter :\expandafter =\@fps
217       \do
218       {%
219         \if \reserved@a h%
220           \ifodd \@tempcnta
221         \else
222           \advance \@tempcnta \@ne
223         \fi
224         \else\if \reserved@a t%
225           \@setfpsbit \tw@
226         \else\if \reserved@a b%
227           \@setfpsbit 4%
228         \else\if \reserved@a p%
229           \@setfpsbit 8%
230         \else\if \reserved@a !%
231           \ifnum \@tempcnta>15
232             \advance\@tempcnta -\sixt@@n\relax
233           \fi
234         \else
235           \@latex@error{Unknown float option `\'reserved@a'}%
236           {Option `\'reserved@a' ignored and `p' used.}%
237           \@setfpsbit 8%
238         \fi\fi\fi\fi\fi
239       }%
240       \@tempcntb \csname ftype@\@cuptype \endcsname

```

```

241      \multiply \@tempcntb \@xxxii
242      \advance \@tempcnta \@tempcntb
243      \global \count\@currbox \@tempcnta
244      }%
245      \@fltovf
246 \fi

```

This starts the structure for the float.

```

247 \csname __tag_float_init:\endcsname
248 \UseTaggingSocket{float/begin}%
249 \global \setbox\@currbox
250   \color@vbox
251   \normalcolor
252   \vbox \bgroup
253     \hsize\columnwidth
254     \@parboxrestore
255     \@floatboxreset

```

We add a target for links. TODO: check that it doesn't affect spacing!!

```

256      \MakeLinkTarget*{\@capytype.struct.\@current@float@struct}%
257 }%

```

The end code of the float ...

```

258 \def\end@float{%
259   \@endfloatbox
260   \UseTaggingSocket{float/end}%
261   \ifnum\@floatpenalty <\z@
262     \@largefloatcheck
263     \@cons\@currlist\@currbox
264     \ifnum\@floatpenalty <-\@Mii
265       \penalty -\@Miv
266       \@tempdima\prevdepth
267       \vbox{}%
268       \prevdepth\@tempdima
269       \penalty\@floatpenalty
270     \else
271       \vadjust{\penalty -\@Miv \vbox{}\penalty\@floatpenalty}\@Esphack
272       \UseTaggingSocket{float/hmode/end}%
273     \fi
274   \fi
275 }

```

and similar for double floats:

```

276 \def\end@dblfloat{%
277   \if@twocolumn
278     \@endfloatbox
279     \UseTaggingSocket{float/end}%
280     \ifnum\@floatpenalty <\z@
281       \@largefloatcheck
282       \global\dp\@currbox1sp %
283       \@cons\@currlist\@currbox
284       \ifnum\@floatpenalty <-\@Mii
285         \penalty -\@Miv
286         \@tempdima\prevdepth

```

```

287     \vbox{}%
288     \prevdepth\@tempdima
289     \penalty\@floatpenalty
290   \else
291     \vadjust{\penalty -\@Miv \vbox{ }\penalty\@floatpenalty}\@Esphack
292     \UseTaggingSocket{float/hmode/end}%
293   \fi
294 \fi
295 \else
296   \end@float
297 \fi
298 }%
299 \ExplSyntaxOn

```

6.7 Handling captions

6.7.1 (Tagging) sockets

These sockets are in `ltagging`: `caption/begin` (1 argument), `caption/end`, `caption/label/begin`, `caption/label/end`.

caption/label (*socket*) This socket is a lightweight start for some interface to format the label or add a font command. The argument is the label text. The default plug `kernel` adds a colon and a space. TODO: revisit after checking float and caption packages to identify which sockets and hooks are needed.

```

300 \NewSocket{caption/label}{1}

```

kernel (`caption/label`) (*plug*) The standard label formatting from the kernel.

```

301 \NewSocketPlug{caption/label}{kernel}
302 {
303   #1:~
304 }
305 \AssignSocketPlug{caption/label}{kernel}

```

default (*plug*) The caption begin socket takes an argument: the structure number of the parent float. If the argument is empty, the current structure is used. TODO: a `tagpdf` key that moves a structure to the begin of the parent. The caption is moved to the first position with the `firstkid` option.

```

306 \NewTaggingSocketPlug{caption/begin}{default}
307 {
308   \tl_if_empty:eTF {#1}
309   {
310     \tag_struct_begin:n{tag=\UseStructureName{float/\@capttype/caption},firstkid}
311   }
312   {
313     \tag_struct_begin:n{tag=\UseStructureName{float/\@capttype/caption},parent=#1,firstkid}
314   }
315   \bool_set_true:N \l__tag_para_flattened_bool
316 }
317 \AssignTaggingSocketPlug{caption/begin}{default}

```

```

default (plug)
318 \NewTaggingSocketPlug{caption/end}{default}
319 {
320   \tag_struct_end:
321 }
322 \AssignTaggingSocketPlug{caption/end}{default}

ort/caption/label/begin) (plug)
323 \NewTaggingSocketPlug{caption/label/begin}{default}
324 {
325   suppress para tagging at the begin.
326   \tagpdfparaOff
327   \tag_struct_begin:n{tag=\UseStructureName{float}/\@capttype/label}}
328   \tag_mc_begin:n{}
329 \AssignTaggingSocketPlug{caption/label/begin}{default}

pport/caption/label/end) (plug)
330 \NewTaggingSocketPlug{caption/label/end}{default}
331 {
332   \tag_mc_end:
333   \tag_struct_end:
334   \tagpdfparaOn
335 }
336 \AssignTaggingSocketPlug{caption/label/end}{default}

```

6.7.2 Redefinitions

With hyperref that means that the `\refstepcounter` now can affect spacing so we change that to the kernel `refstepcounter`:

```

337 \def\caption{%
338   \ifx\@capttype\@undefined
339     \latex@error{\noexpand\caption\c_space_tl outside~float}\@ehd
340     \expandafter\@gobble
341   \else

```

if a caption is used outside a float no target has been set and `\@current@float@struct` is empty

```

342   \tl_if_empty:NTF\@current@float@struct
343   {
344     \refstepcounter\@capttype
345   }
346   {
347     \@kernel@refstepcounter\@capttype

```

we need to reset the target for `\addcontentsline`. We use `\@capttype` to support autoref.

```

348     \xdef\@currentHref{\@capttype.struct.\@current@float@struct}%
349   }
350   \expandafter\@firstofone
351   \fi
352   {\@dblarg{\@caption\@capttype}}%
353 }

```

`\@makecaption` `\@makecaption` is defined by the classes so we overwrite it for now at begin document.

```

354 \NewHookWithArguments{cmd/\@makecaption/before}{2}
355 \AddToHook{begindocument}
356 {
357   \long\def\@makecaption#1#2{%
358     \UseHookWithArguments{cmd/\@makecaption/before}{2}{#1}{#2}%
359     \vskip\abovecaptionskip

```

We don't want tagging when storing the caption for the singleline check.

```

360     \SuspendTagging{\@makecaption}
361     \sbox\@tempboxa{\UseSocket{caption/label}{#1}{#2}%
362     \ResumeTagging{\@makecaption}

```

We pass `\@current@float@struct` as parent structure number. If that is empty the socket will use the parent structure and hope ...

```

363     \UseTaggingSocket{caption/begin}{\@current@float@struct}
364     \ifdim \wd\@tempboxa >\hsize
365       \UseTaggingSocket{caption/label/begin}
366       \UseSocket{caption/label}{#1}
367       \UseTaggingSocket{caption/label/end}
368       \UseTaggingSocket{para/begin}
369       #2
370     \par
371     \else

```

we don't reuse the box as it doesn't contain tagging, but set the text explicitly.

```

372       \global \@minipagefalse
373       \hb@xt@\hsize{\hfil
374         \UseTaggingSocket{caption/label/begin}
375         \UseSocket{caption/label}{#1}
376         \UseTaggingSocket{caption/label/end}
377         \UseTaggingSocket{para/begin}
378         #2
379         \UseTaggingSocket{para/end}
380         \hfil}%
381       \fi
382       \UseTaggingSocket{caption/end}
383       \vskip\belowcaptionskip}
384   }

```

(End of definition for \@makecaption. This function is documented on page 4.)

```

385 \end{package}

```