

The `latex-lab-math` code^{*}

Frank Mittelbach, Joseph Wright, L^AT_EX Project

v0.7j 2026-10-15

Abstract

This module handles the tagging of math. It adapts the `math` command and switches to capture math material and then tag this material.

Contents

1	Introduction	2
2	Math capture	3
3	Avoiding math capture	3
3.1	Options to suppressing math capture and tagging	3
3.1.1	Using the trigger token <code>\m@th</code> <i>inside</i> the math	4
3.1.2	Using <code>\m@th</code> <i>before</i> the opening <code>\$</code>	4
3.1.3	Disabling math tagging with <code>\MathCollectFalse</code>	5
4	Math capture interfaces	5
4.1	Code level interfaces	5
4.2	Document level interfaces	5
5	Math tagging	6
5.1	Code requirements	6
5.2	Inline math	6
5.3	Display math	7
5.4	Associated Files	7
5.5	MathML in an attribute	8
5.6	Automatic mathml creation with <code>luamml</code>	8
5.7	Summary of math options	9
6	Debugging	11
7	Known current bugs, etc.	11
7.1	Capture/grabbing problems	11
7.2	Fake math	12
7.2.1	Open problems	12
7.3	Processor	12
7.4	Other problems	13
7.5	Other Todos	13

*

8	The Implementation	13
8.1	File declaration	13
8.2	Setup	13
8.3	Debugging	14
8.4	Data structures	14
8.5	Math attributes	15
8.6	Code related to AF	15
8.7	Mathstyle detection	25
8.8	Tagging options	26
8.8.1	Meta keys	26
8.9	Sockets	28
8.9.1	Main inline math sockets	28
8.9.2	Main display math sockets	28
8.9.3	Sockets plugs for tags (labels)	29
8.9.4	Internal sockets	30
8.10	Interface commands	34
8.11	Content grabbing	35
8.12	Token-by-token inline grabbing	37
8.13	Marking math environments	39
8.14	Regaining control after a display has finished with \$\$	41
8.15	Document commands	44
8.16	<code>\everymath</code> and <code>\everydisplay</code>	45
8.17	Modifying kernel environments	46
8.18	Modifying kernel commands	46
8.19	Disable math grabbing in the <code>begindocument</code> hook	49

Index	49
--------------	-----------

1 Introduction

Tagging math involves a variety of tasks that require that math is captured before the typesetting:

- When typesetting the math MC-tags and structure commands must be inserted at the begin and the end, and perhaps also around lines or other subparts of the equation.
- The source and/or a MathML-representation of the source must be available so that it can be (perhaps after some preprocessing) be used in an associated file or in an alternate text.
- It should be possible to measure the math for, e.g., a `bbox` setting.

This file implements capture of all math mode material at the outer level, i.e., a formula is captured in its entirety with inner text blocks (possibly containing further math) absorbed as part of the formula. For example,

```
\[ a \in A \text{ for all } a<5\$ \]
```

would only result in a single capture of the tokens “`a_\in A_\text{\_for\_all\_}a<5\$`”.

2 Math capture

In the current setup

- `$`, `\(...\)`, `\[...\]` and `$$` grab (eventually through a command in `\everymath`/`cseverydisplay`) if the boolean `\l_@@_collected_bool` is false. If the boolean is true they behave normally and can for example contain verbatim.
- All (registered) environments grab their body regardless of the state of the boolean. For `equation`, `equation*` and `math` this is a change as they no longer can contain verbatim.

3 Avoiding math capture

In most cases when an environment or command switches into math, the semantic meaning of the content *is* math and grabbing and then tagging that as a Formula is adequate.

But there are exceptions, most prominently with the math shift token `$`.

- `$` can be used to center a box with `\vcenter`, for example, in the tabular code¹. The opening `$` is then often in a different command than the closing `$` and the content of the box should be tagged normally, including all math it contains. This means one wants to avoid that the opening `$` triggers the math grabbing and creates a Formula structure, and after the `$` one wants to switch back to normal text and math capture/tagging.
- `$` is used to place superscripts and subscripts, see the definition of `\textsuperscript` which uses `\ensuremath` internally². Inside the superscript in special cases you may want more tagging (including nested math tagging) but typically it is simple text.
- `$` is used to access a char in a math font.

For example the `\meta` command uses internally the math commands `\langle` and `\rangle` around its argument:

`$_\langle\textit{argument}\rangle_$_` which gives $\langle argument \rangle$.

The symbols are then clearly not math. (Beside disabling math tagging one could also use text commands like `\textlangle` and `\textrangle`: $\langle argument \rangle$. Depending on the font that could even look better, but it requires that the font supports the chars, which is not the case for various OpenType fonts.) Additional tagging inside the math should be not needed. If the symbols need an actual text then a Span can be added around the whole material.

3.1 Options to suppressing math capture and tagging

We are therefore providing a number of options to suppress the collection/grabbing of the math and with it the tagging. These commands can be used to control locally the tagging of math. The first two are new commands. `\math` is a standard L^AT_EX command used in a number of places to set `\mathsurround` to zero; with active tagging it is also used to identify math that should not be tagged, because it has traditionally be used

¹This will change in L^AT_EX 2026-06-01. The tabular code will then no longer use `\vcenter` and math

²This will change in L^AT_EX 2026-06-01. `\textsuperscript` and `\textsubscript` will no longer use math mode.

in exactly the places where math mode is used for its layout characteristics and not for representing a formula.³ Details are described below. (`\SuspendTagging` is documented in source2e.pdf.)

To set `\mathsurround` without disabling math tagging, use `\mathsurround\z@` directly.

3.1.1 Using the trigger token `\m@th` *inside* the math

If the grabbed math contains the token `\m@th` the tagging/processing of the math is suppressed. As the math is nevertheless grabbed, this requires that the end math shift token is not hidden in some other command. `\m@th` sets also `\mathsurround` to zero, which is often wanted in untagged math anyway.

Text tagging is *not* suppressed inside the math, e.g., `\mbox{\emph{text}}` will still create an Em-structure. In contrast nested math is not tagged.

To suppress the text tagging `\SuspendTagging{}` can be used:

- no math tagging, but `\emph` is tagged:

$$\text{\m@th\langle\mbox{\emph{if and only if}}\, $x=y$}\rangle$}$$
- no internal tagging:

$$\text{\m@th\SuspendTagging{}\langle\mbox{\emph{if and only if}}\, $x=y$}\rangle$}$$

The method is quite suitable for symbols and also for sub- and superscripts (as long as they don't contain nested math that should be tagged).

3.1.2 Using `\m@th` *before* the opening `$`

`\m@th` (as defined in the latex-lab-math code) sets also the internal boolean which controls the grabbing to true and so when it is used *before* some math it disables math grabbing and tagging for all following math in the current group (including nested math). Text tagging inside the math is still active, it can be disabled as above with `\SuspendTagging{}`.

When `\m@th` is used like this it is possible to reenale the math tagging of nested math, by adding `\MathCollectTrue` after the opening `$`.

- no math tagging, but `\emph` is tagged:

$$\text{\m@th$\langle\mbox{\emph{if and only if}}\, $x=y$}\rangle$}$$
- both nested math and `\emph` is tagged:

$$\text{\m@th$\MathCollectTrue\langle\mbox{\emph{if and only if}}\, $x=y$}\rangle$}$$

The method is suitable for symbols and sub- and superscripts too (it is actually how superscripts avoid math tagging before L^AT_EX 2026-06-01). It can also be used in cases where the end math shift token is hidden in some other command. But it is not so useful for larger boxes as it sets `\mathsurround` to zero. Grouping should be used to avoid side-effects on following math.

³This way even code that is not adjusted up for tagging is handled correctly if it uses `\m@th`.

3.1.3 Disabling math tagging with `\MathCollectFalse`

Without a side-effect on `\mathsurround` the math grabbing can be suppressed and reenabled by setting the boolean that controls the collecting. So in the following example the math in the `\mbox` is properly tagged, but the angled brackets are simple text.

```
%stop math grabbing
\MathCollectFalse
$
%(optional) restart math grabbing for nested math
\MathCollectTrue
\langle\mbox{\emph{if and only if}} $x=y$ \rangle
$
%(optional) restart math grabbing for following math
% if there is no grouping
\MathCollectTrue
\quad $x=1$
```

The method is suitable if a box should be centered with `\vcenter` (and before L^AT_EX 2026-06-01 was used in `array.sty` for the tabular code).

4 Math capture interfaces

4.1 Code level interfaces

<code>\math_register_env:n</code>	<code>\math_register_env:n {<env>}</code>
<code>\math_register_env:nn</code>	<code>\math_register_env:nn {<env>} {<options>}</code>

Registers the `<env>` as a math environment which should be captured and made available. This is necessary for all top-level math mode environments: low-level errors may result if these are not correct set up. One or more key-value `<options>` may also be given:

arg-spec The argument specification taken by the beginning of the environment; this is used to remove non-mathematical material.

<code>\math_processor:n</code>	<code>\math_processor:n {<tokens>}</code>
--------------------------------	---

Declares that the captured math content should be passed to the `<tokens>`, which will receive the environment type as `#1` and the content as `#2`. The processing is done before the typesetting. It is not applied if `\ifmeasuring@` is true.

4.2 Document level interfaces

<code>\RegisterMathEnvironment</code>	<code>\RegisterMathEnvironment [<options>] {<env>}</code>
---------------------------------------	---

Registers the `<env>` as a math environment which should be captured and made available. This is necessary for all top-level math mode environments: low-level errors may result if these are not correct set up. One or more key-value `<options>` may also be given:

arg-spec The argument specification taken by the beginning of the environment; this is used to remove non-mathematical material.

<code>\MathCollectTrue</code>	<code>\MathCollectTrue</code>
<code>\MathCollectFalse</code>	<code>\MathCollectFalse</code>

This activates/deactivates the math collection of the math shift token. See above for cases when this can be useful.

5 Math tagging

5.1 Code requirements

The tagging code has to handle

- the embedding into the surrounding. This means
 - closing and reopening MC-chunks
 - closing and reopening text/P-structures
 - handling interferences of the tagging code with penalties and spacing.
- the actual tagging which means to do some or all of the following tasks:
 - setup content for an associated source file
 - setup content for an associated MathML file
 - setup content for the /Alt key
 - setup content for the /ActualText key
 - setup attributes
 - add associated files
 - add a Formula structure
 - surround elements of the equation with MathML structure elements (currently only luatex with luamml)

5.2 Inline math

The embedding code is added through the tagging sockets

- `math/inline/begin`
- `math/inline/end`

The sockets simply push and pop the MC currently. Without tagging they use the noop-plug.

The actual tagging is in done through the tagging sockets

- `math/inline/formula/begin` This socket takes the math as second argument and its code should output it for typesetting. The `default` plug of the socket calls these three internal sockets for the tagging support:
 - `math/content` This should set up the various content variables (empty variables are ignored by the structure code and so can be used to suppress a setting).
 - `math/struct/begin` This calls `\tag_struct_begin:n`. It should also write the associated files if needed.

- `math/inline/formula/end` This socket ends the formula structure(s). The default plug calls this internal socket:

– `tagssupport/math/struct/end`

5.3 Display math

to be written

5.4 Associated Files

The current code allows the attachment of two types of associated file to the Formula structure: the L^AT_EX source and a MathML representation. Technically both can be attached—AF is an array of file references—in practice there can be problems with PDF consumers: e.g., ngpdf used both and so showed the equation twice (this has been corrected in the newest version) and Foxit seems to see only the first AF in the array (so we attach the MathML as the first file).

The L^AT_EX source can be (and is) attached automatically. It can be suppressed by an option with `math/tex/AF=false`, see below.

The MathML is attached if the files `\jobname-mathml.html` and/or `\jobname-luamml-mathml.html` are found and if they contains a suitable MathML snippet for the current formula. If the files contain more than one suitable snippet (as identified by the hash) the first one is used. `\jobname-luamml-mathml.html` is automatically generated (see below section 5.6) and read after `\jobname-mathml.html`. This means that `\jobname-mathml.html` can contain improved versions of a formula.

The MathML processing can be suppressed globally by emptying the list of mathml files with `math/mathml/sources=`. Locally for a formula `math/mathml/AF=false` can be used.

For a MathML representation a file with such representations must be provided. If the equation is numbered the numbering should be part of the MathML as the Lb1 substructure is ignored if an MathML is used (see https://github.com/foxitsoftware/PDF_UA-2).

The MathML representation is given in a special format. It is meant to be a valid html file that can be viewed in a browser. For this it can start with `<!DOCTYPE html><html>` and end with `</html>` It should have the extension `.html`. The `<mathml>` content is read with special catcodes, so can contain ambersands, hashes, comment chars and unmatched braces such as `<mo>{</mo>`

The file should contain a number of representations in this format:

```
<div>
  <h2>\mml <key></h2>
  <p><source></p>
  <p><hash></p>
  <math <attributes> >
    <mathml>
      </math>
</div>
```

The keywords `<div>`, `<h2>\mml`, `<p>`, `<math>`, `</math>` `</div>` are required as they are used to delimit the arguments by the L^AT_EX code.

$\langle key \rangle$ and $\langle source \rangle$ are only used for debugging, they help to identify the equation referred by this representation. The source should be used correctly escaped $\&$ and $<$ so that it gives valid html!

$\langle attributes \rangle$ is not required either, but can, e.g., contain attributes to improve the display in a browser:

```
<math alttext="\mathbf{G}" class="ltx_Math" display="inline">
```

It can also contain the name space declaration:

```
xmlns="http://www.w3.org/1998/Math/MathML"4
```

By default the code tries at the begin of the document to read a file $\backslash jobname-mathml.html$ in the html-format. The file name can be changed with

```
mathml/setfiles={filename1,filename2}
```

(without extension, `html` is added automatically). If there is a list, all files are loaded. If a file doesn't exist it is ignored, only an info is written to the log.

Currently every MathML-snippet from a file is embedded into the PDF, it is not checked first if it is actually used (simply writing everything to the PDF is a bit easier than keeping everything in memory and also means that the snippets are one after the other in the PDF).

As mentioned above the MathML-AF can be suppressed for the equations in a group with `math/mathml/AF=false`, or completely by setting `math/mathml/sources=` in the preamble.

Files embedded in a PDF can be listed in the attachments panel of a PDF viewer. This is probably not so useful for lots of small files (but one could create collections), but as long as PDF editors or viewers don't offer proper support to access the AF it can help so have them there. The MathML are added by default, but the $\LaTeX$ source not. This can be changed with `viewer/pane/mathsourcetrue` (anywhere in the document) and `viewer/pane/mathml=false` (in the preamble, before the external file is read).

5.5 MathML in an attribute

Microsoft Word puts the MathML into a proprietary attribute. For testing purpose this is implemented here too. The writing of such an attribute can be activated globally with `tagging-setup={math/setup=mathml-MS}`. Locally it can be disabled with `math/MS/use=false`. The code makes use of the exported MathML file, so it needs two compilation and will not work if embedding of MathML is disabled.

5.6 Automatic mathml creation with luamml

If `lualatex` and one of the packages `unicode-math` or `lua-unicode-math` is used, the package `luamml` is loaded and this package will then automatically generate the file $\backslash jobname-luamml-mathml.html$ with MathML representations of all math formulas. This file is then used in subsequent compilations and works also with `pdflatex`.

The generation of the file can be suppressed (in the preamble) with `math/mathml/luamml/write=false`.

If neither `unicode-math` or `lua-unicode-math` are used, the loading of `luamml` and with it the generation of the file can be forced with `math/mathml/luamml/load=true`

⁴But it is probably not needed and only blows up the PDF.

or `math/mathml/luamml/write=true` but be aware that it is then possible that various symbols are mapped to the wrong Unicode code points.

The package `luamml` is still quite experimental and the output should be checked. The `\jobname-luamml-mathml.html` file may be previewed in a browser although you may need to add additional css or javascript declarations to enable browser support for all MathML constructs.

5.7 Summary of math options

The following options exist to make math more accessible:

ActualText An **ActualText** can be placed on structure elements, but can also be added in the stream on a BDC marker with a **Span** tag (normally an independent marker without an MCID number, it is not clear yet if it can be used on an MC-chunk). The content is a text string, typically one or a few Unicode characters. **ActualText** is meant to replace the content and should only be used on small entities, e.g., to define the semantic or the Unicode code point of a symbol. **ActualText** is not supported by all PDF reader. It is also unknown where it should be used at best (in a structure element, or on an independent Span-BDC) and what happens if it is used in more than one place.

enabled by default? False

how to enable/disable No interface yet. **ActualText** can only be added on the Formula structure element by changing the `tagssupport/math/content` or some other socket. For a BDC marker one can, e.g., use

```
\pdf_string_from_unicode:nnN{utf16/hex}{€}\l_tmpa_tl
\pdf_bdc:ee{Span}{/ActualText\l_tmpa_tl}content\pdf_emc:
```

There should be no page break in the *content* and the BDC should be correctly nested into tagging, so, e.g., a `\leavevmode` should be issued before the bdc command.

Consumer support in part and in part buggy, needs tests ...

Alt Like **ActualText** the **Alt** key can be used on structure elements and on **Span** in the stream. It should contain a description of the content and is mainly meant for images. PDF/UA-1, which views math formulas as illustrations, mandates the key also for Formula structure elements.

enabled by default? false unless PDF/UA-1 is detected, then it is enabled in the `begindocument/end` hook (this will be reconsidered when it is clear, that the use of **Alt** does not shadow MathML). It can be enabled for all engines and PDF versions.

enable/disable `\tagpdfsetup{math/alt/use}` (local boolean, so can be used on individual equations)

default value A template text (stored in `\l_@@_content_template_tl`) starting with LaTeX formula starts.

user value No interface currently provided. This needs optional arguments or an external setup command. See <https://github.com/latex3/tagging-project/discussions/717>.

source-AF The $\text{\LaTeX}$ -source of the equation can be attached as an associated file with mime-type application/Fx-tex. The `AFRelationship` is `Source`. The source is embedded without expansion. This means that targets of references and macros are not resolved. The files are by default not shown in the EmbeddedFiles pane, this can be enabled with `viewer/pane/mathsource=true`. If an A-standard is used, it must be one that allows embedded files, e.g., A-4f.

enabled by default? true for all engines and PDF versions

enable/disable `\tagpdfsetup{math/tex/AF}` (local boolean, so can be used on individual equations)

default value source code including dollars or environment name.

consumer support Currently only ngpdf makes use of it: if there is no MathML it passes the source to mathjax.

luamml The following options make (with `lualatex`) use of the `luamml` package. `luamml` is currently automatically loaded (at the end of the preamble) if `unicode-math` or `lua-unicode-math` has been detected. The loading can be forced or suppressed with `\tagpdfsetup{math/mathml/luamml/load=true/false}`.

`luamml` affects all math, locally it can be stopped with `math/mathml/ignore`, or by using the commands described in the package.

mathml-AF A MathML representation of the equation can be attached to the structure. The configuration possibilities are rather complex as the keys have to control three different aspects: The *generation* of the file with the MathML fragments, the *reading* and *embedding* of the MathML fragments, and the *association* of a MathML fragment to a specific equation.

generation With `pdf $\text{\LaTeX}$` MathML fragments can not be generated automatically, but a file with dummy fragments for every equation will be written if `\tagpdfsetup{math/mathml/write-dummy}` is issued in the preamble.

With `lua $\text{\LaTeX}$` a file with MathML fragments will be created automatically if the package `luamml` has been loaded (see above).

reading and embedding By default the code will read and embed MathML from `\jobname-mathml.html` and `\jobname-luamml-mathml.html` in this order and the first fragment with a new hash value will be inserted. The list of sources and their order can be changed with the key `math/mathml/sources`, setting that to an empty value suppresses the loading MathML associated files completely. For efficiency reasons it embeds math fragments directly, there is no check yet if the fragment is actually used.

The files are by default shown in the EmbeddedFiles pane, this can be disabled with `viewer/pane/mathml=false`.

attaching A MathML fragment is currently attached as an associated file to a Formula if the hash of the source matches the hash of the fragment. This is not a perfect test: equations with the same source and so the same hash can have different MathML representation, e.g., if there are references or commands or counters in the equation. This will change in a future version. The attachment can be suppressed locally with `math/mathml/AF=false`. The MathML fragment will still be embedded in the PDF!

TODO: adapt test

mathml structure elements MathML structure elements can be used in PDF 2.0 directly. In PDF 1.7, one could theoretically use them if one declares a role mapping first, (this can be done with `\tagpdfsetup{role/mathml-tags}`) which maps all to `Span`. But such a role mapping breaks the reading and with it the accessibility of the math, as only `Span` is passed to the screen readers and so it is not recommended. Automatic generation of structure elements is only possible with `lualatex`. It requires that the package `luamml` has been loaded.

enabled by default? false

enable/disable `\tagpdfsetup{math/mathml/structelem}` (local setting, so can be used with grouping on individual equations).

consumer support Needs more tests.

6 Debugging

```
\DebugMathOn
\DebugMathOff
\math_debug_on:
\math_debug_off:
```

These commands enable/disable debugging messages.

7 Known current bugs, etc.

7.1 Capture/grabbing problems

1. Incorrect grabbing of $\$$ -math when there is also explicit $\$$ -math within a *text environment* that is itself within the math that should all be grabbed. For example,

$$\$a\begin{minipage}{1cm}\$b\end{minipage}\$$$

would only result in the capture of the tokens “`a\begin_{minipage}{1cm}`”. This can be avoided by an additional brace group:

$$\${a\begin{minipage}{1cm}\$b\end{minipage}}\$$$

2. Similar incorrect grabbing with $\$$ $\$$ also.
3. The grabbing, for all the display environments (and `\` `\]`), needs to deal with nesting: `amsmath` contains code for this.
4. The math can’t contain verbatim and verbatim-like commands. This is nothing new for the `amsmath` environments but changes $\$$ and `\[` `\]` and `equation*` (see, e.g., tagging-project issue #30).
5. Begin and end of the math or math environment can not be hidden in commands. For example `>\$1<\$` in a tabular would lead to errors. Therefore in a tabular a slower token-by-token grabbing is used.

7.2 Fake math

For the current state see 3 above. The text here is mainly kept for history.

In a number of places in L^AT_EX math commands (mainly `$`) is used only for technical reason, e.g., to access a math font, to setup a symbol or to use `\vcenter`.

The code identifies such fake math mostly by making use of the `\m@th` command where two methods are used for the automatic detection:

- After grabbing math content the code checks if the content contains the token `\m@th` and if yes it doesn't call the processor before reinserting the content and perhaps adding tagging code. This method requires that the math can be grabbed (e.g. that the end dollar is visible) and that the `\m@th` is visible. It applies for example in `\@iiiparbox` where the code from `$\vcenter` to `\m@th$` is grabbed and put back. It does not work for example for `tabular` where the dollars and the `\m@th` token are spread around over three commands. `tabular` needs therefore manual intervention. A look in the list of usages (in `usage-of-m@th.md`) justifies this approach. All usages are either not math at all, or related to small elements that probably shouldn't be grabbed and processed on their own.
- `\m@th` is redefined so that it sets the boolean `\l_@@_collected_bool` to true. If `\m@th` is used inside math that has been grabbed this doesn't change much as the boolean is set by the grabbing anyway. For usages outside math the benefit is not so clear: The setting avoids that in L^AT_EX_ε the epsilon is processed as math, but it also prevents that the content of the amsmath command `\boxed` is processed as math. It means that if one wants to reenale math processing inside some (fake) math one has to do it after `\m@th` calls.

7.2.1 Open problems

1. The grabbing code doesn't pass the info that it detected a `\m@th` token. This means that the tagging code has to do the same check (and doesn't do this in all cases yet).
2. Commands are missing to locally disable the grabbing and processing, e.g., to handle `tabular`.
3. It must be checked if setting the boolean in `\m@th` really makes sense or if commands like L^AT_EX_ε should be handled manually.

7.3 Processor

The grabbed math is at first passed to the processor. The processor is not called in a measuring phase (from the amsmath `\ifmeasuring@`) and if the `\m@th` token is detected. It is not quite clear what purpose the processor has. As it is a public interface it can't be used for internal code. And typesetting happens later and the processor can't really change this. Currently it is mostly used for debugging and messages. If the `\m@th` is found the `\l_@@_fakemath_bool` is set, so if the code is changed this must be preserved.

7.4 Other problems

1. The presence of `\math` in association with `\ensuremath` does not necessarily indicate fake math. This is because wanting `mathsurround` to be zero is very reasonable and common, *even when the math is genuine* (and hence needs to be collected).
TODO: this claim needs some examples.
2. User-defined environments can create problems; but this area, of new, copied and changed environments, has not yet been developed.

Joseph wrote, inter alia:

My thinking [regarding] `\RegisterMathEnvironment`

- (New) Math environments should not be created-then-patched, but only generated by a [(future)] dedicated command (`\DeclareMathEnvironment`, presumably)
- Math environments created with `ltxcmds` [commands] should not be copied, . . .
- Package authors should be able to manually set up math environments with a public boolean.

7.5 Other ToDos

1. Add (some of) the math display commands that were “lifted from plain”, e.g., `\displaylines` `\eqalign`(??).
2. The `breqn` packages changes catcodes and that isn’t yet covered by our mechanism.
3. `\intertext` is not correctly taken into account by the code splitting multiline math into subformulas.

`\MaybeStop` (temporarily) not executed, as it is unknown on Chris’ system.

8 The Implementation

1 `<*kernel>`

8.1 File declaration

```
2 \ProvidesFile{latex-lab-math.ltx}
3           [\ltxlabmathdate\space
4           v\ltxlabmathversion\space
5           Grab all the math(s) and tag it]
6 <@@=math>
7 \ExplSyntaxOn
```

8.2 Setup

Loading `amsmath` is an absolute requirement: this avoids needing to have conditional definitions and deals with how to define `\[/\]` neatly. The package is loaded before `lua-unicode-math` or at begin document to allow user to load it with options.

```
8 \AddToHook{package/lua-unicode-math/before}{\RequirePackage { amsmath }}
9 \AddToHook{begindocument/before}{ \RequirePackage { amsmath } }
```

8.3 Debugging

```

\g__math_debug_bool
10 \bool_new:N \g__math_debug_bool

__math_debug:n
__math_debug_typeout:n
11 \cs_new_eq:NN \__math_debug:n \use_none:n
12 \cs_new_eq:NN \__math_debug_typeout:n \use_none:n

(End of definition for \__math_debug:n and \__math_debug_typeout:n.)

\math_debug_on:
\math_debug_off:
__math_debug_gset:
13 \cs_new_protected:Npn \math_debug_on:
14 {
15   \bool_gset_true:N \g__math_debug_bool
16   \__math_debug_gset:
17 }

18 \cs_new_protected:Npn \math_debug_off:
19 {
20   \bool_gset_false:N \g__math_debug_bool
21   \__math_debug_gset:
22 }

23 \cs_new_protected:Npn \__math_debug_gset:
24 {
25   \cs_gset_protected:Npe \__math_debug:n ##1
26   { \bool_if:NT \g__math_debug_bool {##1} }
27   \cs_gset_protected:Npe \__math_debug_typeout:n ##1
28   { \bool_if:NT \g__math_debug_bool { \typeout{[Math]~ ==>~ ##1} } }
29 }

(End of definition for \math_debug_on:, \math_debug_off:, and \__math_debug_gset:. These functions
are documented on page 11.)

```

\DebugMathOn If we are debugging blocks we also want to know about template instances, so we turn
\DebugMathOff the debugging for templates as well (for now).

```

30 \cs_new_protected:Npn \DebugMathOn { \math_debug_on: }
31 \cs_new_protected:Npn \DebugMathOff { \math_debug_off: }

32 \DebugMathOff

```

(End of definition for \DebugMathOn and \DebugMathOff. These functions are documented on page 11.)

8.4 Data structures

\l__math_collected_bool Tracks whether math mode material has been collected, which happens inside `amsmath` environments as well as those handled directly here. If true following math will not grab and/or process. See 2 for details.

```

33 \bool_new:N \l__math_collected_bool

```

<code>\l__math_fakemath_bool</code>	Tracks whether math mode material has been identified as fake math during the grabbing phase, which happens currently if the grabbed contents contains the <code>\m@th</code> token.
-------------------------------------	--

```
34 \bool_new:N \l__math_fakemath_bool
```

<code>\l__math_math_content_artifact_bool</code>	Tracks whether math content should be marked as artifact by default.
--	--

```
35 \bool_new:N \l__math_math_content_artifact_bool
```

Change first tl name below: 'env' => 'info'?

Or do we need an extra

storage

`\g__math_grabbed_env_tl` contains the name of the math environment (`math` in the case of inline math, `\g__math_grabbed_math_tl` the math content).

```
36 \tl_new:N \g__math_grabbed_env_tl
```

```
37 \tl_new:N \g__math_grabbed_math_tl
```

<code>\l__math_tmpa_tl</code>	Temporary variables
<code>\l__math_tmpa_skip</code>	
<code>\l__math_tmpa_str</code>	

```
38 \tl_new:N \l__math_tmpa_tl
```

```
39 \skip_new:N \l__math_tmpa_skip
```

```
40 \str_new:N \l__math_tmpa_str
```

<code>\l__math_content_alt_tl</code>	Temporary variables to hold math content that should be used in actual or alt text and stored as AF.
<code>\l__math_content_actual_tl</code>	
<code>\l__math_content_AF_tl</code>	

```
41 \tl_new:N \l__math_content_alt_tl
```

```
42 \tl_new:N \l__math_content_actual_tl
```

```
43 \tl_new:N \l__math_content_AF_source_tl
```

```
44 \tl_new:N \l__math_content_AF_source_tmpa_tl
```

```
45 \tl_new:N \l__math_content_AF_mathml_tl
```

8.5 Math attributes

The attributes `inline` and `display` are declared in `latex-lab-namespace`. The variable will hold the attribute class.

<code>\l__math_attribute_class_tl</code>
--

```
46 \tl_new:N \l__math_attribute_class_tl
```

8.6 Code related to AF

Booleans to handle the options.

```

\l__tag_math_texsource_AF_bool
\l__tag_math_texsource_pane_bool
\l__tag_math_mathml_AF_bool
\g__tag_math_mathml_AF_bool
\l__tag_math_mathml_pane_bool
\l__tag_math_alt_bool
\g__tag_math_luamml_tl
\l__tag_math_MSFT_bool

```

The variable `\g__tag_math_luamml_tl` is initially 0 and the user key can set it to -1 or 1. This allows to distinguish the unset case from a value set by the user.

```

47 \bool_new:N\l__tag_math_texsource_AF_bool
48 \bool_new:N\l__tag_math_texsource_pane_bool
49 \bool_new:N\l__tag_math_mathml_AF_bool
50 \bool_new:N\g__tag_math_mathml_AF_bool
51 \bool_new:N\l__tag_math_mathml_pane_bool
52 \bool_new:N\l__tag_math_alt_bool
53 \bool_new:N\l__tag_math_MSFT_bool
54 \tl_new:N\g__tag_math_luamml_tl
55 \tl_gset:Nn\g__tag_math_luamml_tl {0}

```

```

\g__math_mathml_total_int
\g__math_mathml_int
\g__math_math_total_int
\g__math_mathml_AF_found_int
\g__math_mathml_AF_attached_int

```

`\g__math_mml_total_int` records the MathML fragments read in. `\g__math_mml_int` records the MathML fragments read in with a different hash. `\g__math_AF_total_int` records the number of math structures that try to attach a mathml AF. `\g__math_AF_found_int` records the number of math structures for which a fitting mathml is found. `\g__math_AF_attached_int` records the number of math structures which got a MathML fragment (if mathml-AF are not disabled locally this should be the equal to the previous number).

```

56 \int_new:N\g__math_mathml_total_int
57 \int_new:N\g__math_mathml_int
58 \int_new:N\g__math_math_total_int
59 \int_new:N\g__math_mathml_AF_found_int
60 \int_new:N\g__math_mathml_AF_attached_int

```

```

\l__tag_math_mathml_files_clist

```

A sequence to store the file list for the MathML. We also check the luamml file.

```

61 \clist_new:N\l__tag_math_mathml_files_clist
62 \clist_put_right:Ne\l__tag_math_mathml_files_clist
63 {\c_sys_jobname_str-mathml,\c_sys_jobname_str-luamml-mathml}

```

This is the internal variant of the `\mml` command.

```

\__math_AF_mml:nnnn

```

```

64 \cs_new_protected:Npn \__math_AF_mml:nnnn #1 #2 #3 #4

```

```

65 %1 number, #2 tex source for debugging, #3 hash, #4 mathml
66 {
67   \int_gincr:N \g__math_mathml_total_int

```

MathML with the same hash should be included only once:

```

68   \tl_if_exist:cF { g__math_mathml_#3_tl }
69   {
70     \int_gincr:N \g__math_mathml_int

```

a simple Desc key, take care that it is a valid string!

```

71     \pdfdict_put:nne {l_pdffile/Filespec} {Desc}{(mathml-#1)}
72     \pdffile_embed_stream:nnN {#4}{mathml-#1.xml}\l__math_tmpa_tl

```

not strictly necessary but makes the files visible in the file attachment page

```

73     \bool_if:NT \l__tag_math_mathml_pane_bool
74     {\pdfmanagement_add:nne {Catalog/Names}{EmbeddedFiles}{\l__math_tmpa_tl}}
75     \tl_new:c{g__math_mathml_#3_tl}
76     \tl_gset_eq:cN{g__math_mathml_#3_tl}\l__math_tmpa_tl
77   }
78 }

```

(End of definition for __math_AF_mml:nnnn.)

This is a version of the previous command which writes MSFT-attributes

```

\__math_MSFT_mml:nn
\__math_MSFT_mml_aux:nn

```

```

79 \cs_new_eq:NN \__math_MSFT_mml:nn \use_none:nn
80 \cs_new_protected:Npn \__math_MSFT_mml_aux:nn #1 #2
81 %1 hash, #2 mathml
82 {

```

mathml with the same hash should be included only once:

```

83   \tl_if_exist:cF { g__math_mathml_MSFT_#1_tl }
84   {
85     \pdf_string_from_unicode:nnN{utf16/hex}{#2}\l__math_tmpa_tl
86     \tag_attr_new:ee
87     {MSFT-#1}
88     {/O /MSFT_Office /MSFT_MathML \l__math_tmpa_tl }
89     \tl_new:c {g__math_mathml_MSFT_#1_tl}
90     \tl_gset:cn {g__math_mathml_MSFT_#1_tl} {MSFT-#1}
91   }
92 }

```

(End of definition for __math_MSFT_mml:nn and __math_MSFT_mml_aux:nn.)

The html reader.

```

93 \cs_new_protected:Npn \__math_AF_html_reader:w#1</h2>#2<p>#3</p>#4<p>#5</p>#6<math{
94   \begingroup
95   \char_set_catcode_other:N{
96   \char_set_catcode_other:N\}
97   \char_set_catcode_other:N\#
98   \char_set_catcode_other:N\%
99   \char_set_catcode_other:N\^
100   \__math_AF_html_reader_verb:w{#1}{#3}{#5}<math
101 }

```

```

102 \cs_new_protected:Npn\__math_AF_html_reader_verb:w#1#2#3#4~</div>{
103   \endgroup
104   \__math_AF_mml:nnnn{#1}{#2}{#3}{#4}
105   \__math_MSFT_mml:nn {#3}{#4}
106   }

```

As with luatex we write two files we define a few constants for the shared texts.

```

\c_math_mathml_write_init_tl
\l_math_mathml_write_before_tl
\c_math_mathml_write_after_tl
\c_math_mathml_write_final_tl
107 \tl_const:Nn \c_math_mathml_write_init_tl
108 {
109   <!DOCTYPE~html>
110   \iow_newline:
111   <html~ xmlns="http://www.w3.org/1999/xhtml">
112   \iow_newline:
113   }
114 \tl_new:N \l_math_mathml_write_before_tl
115 \tl_const:Nn \c_math_mathml_write_after_tl
116 {
117   \iow_newline:
118   </div>
119   \iow_newline:
120   }
121 \tl_const:Nn \c_math_mathml_write_final_tl
122 {
123   </html>
124   }

```

(End of definition for `\c_math_mathml_write_init_tl` and others.)

`mathml/write/prepare` (*tag socket*) To prepare the hash and the starting command we use a socket, so that both the dummy and luamml can make use of it.

```

125 \NewTaggingSocket{math/mathml/write/prepare}{0}

```

On (*plug*)

```

126 \NewTaggingSocketPlug{math/mathml/write/prepare}{0n}
127 {
128   \str_set:NV\l_math_tmpa_str\l_math_content_AF_source_tl
129   \str_replace_all:Nnn\l_math_tmpa_str{&}{&amp;}
130   \str_replace_all:Nnn\l_math_tmpa_str{<}{&lt;}
131   \tl_set:Nn \l_math_mathml_write_before_tl
132   {
133     <div>
134     \iow_newline:
135     <h2>\c_backslash_str mml\c_space_tl \int_use:N \g_math_math_total_int </h2>
136     \iow_newline:
137     <p>\l_math_tmpa_str</p>
138     \iow_newline:
139     <p>\l_math_content_hash_tl </p>
140     \iow_newline:
141   }
142 }

```

With luatex we automatically generate MathML with luamml if the package can be loaded and unicode-math or lua-unicode-math are detected. We start the process in the begindocument/end hook so that the reading from a previous compilation can happen before!

For other engines, for future name changes and in case luamml is not loaded we provide some commands

```

143 \cs_new_protected:Npn\__math_provide_luamml_commands:
144 {
145   \providecommand\luamml_flag_structelem:{}
146   \cs_if_free:NT \luamml_structelem:
147   {
148     \cs_set_eq:NN\luamml_structelem:\luamml_flag_structelem:
149   }
150   \providecommand\luamml_flag_process:{}
151   \cs_if_free:NT \luamml_process:
152   {
153     \cs_set_eq:NN\luamml_process:\luamml_flag_process:
154   }
155   \providecommand\luamml_flag_ignore:{}
156   \cs_if_free:NT \luamml_ignore:
157   {
158     \cs_set_eq:NN\luamml_ignore:\luamml_flag_ignore:
159   }
160 }

161 \sys_if_engine luatex:TF
162 {
163   \AddToHook{begindocument/before}
164   {
165     \str_case:on \g__math_luamml_load_tl
166     {
167       { 1 } {
168         \RequirePackage { luamml }
169         \AddToHook{begindocument/end}
170         {
171           \__math_luamml_activate_write:
172         }
173       }

174       {-1 } {
175         \AddToHook{begindocument/end}
176         {
177           \tag_if_active:T
178           {
179             \msg_note:nnnn { tag }
180             { luamml-status }{ disabled }{ not~create }
181           }
182         }
183       }

184       { 0 }
185       {
186         \bool_lazy_or:nnTF
187         {\cs_if_exist_p:c{ver@unicode-math.sty}}
188         {\cs_if_exist_p:c{ver@lua-unicode-math.sty}}

```

```

189         {
190             \RequirePackage { luamml }
191             \AddToHook{begindocument/end}
192             {
193                 \_math_luamml_activate_write:
194             }
195         }
196         { \msg_warning:nn { tag }{ unicode-math-missing } }
197     }
198 }
199 \_math_provide_luamml_commands:
200 }
201 }
202 {
203     \AddToHook{begindocument/before}
204     {
205         \_math_provide_luamml_commands:
206     }
207 }
208 \msg_new:nnn { tag }{ luamml-status }
209 {
210     luamml~has~been~#1~and~will~#2~a~MathML~file.
211 }
212
213 \msg_new:nnn { tag }{ unicode-math-missing }
214 {
215     Neither~unicode-math~nor~lua-unicode-math~has~been~loaded.\\
216     luamml~will~not~create~a~MathML~file.\\
217     To~avoid~this~warning~load~unicode-math~\\
218     or~lua-unicode-math~or~disable~luamml~with~\\
219     \tl_to_str:n{\tagpdfsetup{math/mathml/luamml/load=false}}\\
220     or~force~luamml~with~\\
221     \tl_to_str:n{\tagpdfsetup{math/mathml/luamml/load=true}}
222 }
223 \cs_new_protected:Npn \_math_luamml_activate_write:
224 {
225     \bool_if:NT \g__math_luamml_write_bool
226     {

```

to avoid that nothing is written in the first run, we must activate the sockets:

```

227     \bool_gset_true:N\g__tag_math_mathml_AF_bool
228     \AssignTaggingSocketPlug{math/struct/begin}{mathml-AF}
229     \AssignTaggingSocketPlug{math/struct/end}{mathml-AF}
230     \int_set:Nn \l__luamml_pretty_int { 7 }
231     \RegisterFamilyMapping\symsymbols{oms}
232     \RegisterFamilyMapping\symletters{oml}
233     \AssignTaggingSocketPlug{math/mathml/write/prepare}{On}
234     \iow_new:N \g__math_luamml_iow
235     \iow_open:Nn \g__math_luamml_iow { \c_sys_jobname_str-luamml-mathml.html }
236     \iow_now:Ne \g__math_luamml_iow { \c__math_mathml_write_init_tl }
237     \cs_new:Npn \_math_luamml_output_hook:n ##1
238     {
239         \tl_if_empty:NF \l__math_mathml_write_before_tl
240         {

```

We check here if the current group level is equal to the one stored for the outer math. We only write output if that is the case.

Currently in L^AT_EX, the `\math@level` is increased for every nested math mode (via `\frozen@everymath`). However, to make the code below work correctly we undo that in the case of “fake math”, i.e., in math mode that is only entered to make use of super or subscript positioning of text or for `\vcentering` text, i.e., if it is not really a “math formula”. We therefore provide a special declaration, `\UseMathForPositioningText`, to indicate that the directly following `$` represents such “fake math”.

```

241         \int_compare:nNnT
242         { \math@level } = { 1 }
243         {
244             \iow_now:Ne \g__math_luauml_iow
245             {
246                 \l__math_mathml_write_before_tl
247                 ##1
248                 \c__math_mathml_write_after_tl
249             }
250         }
251     }
252 }
253 \__luauml_register_output_hook:N \__math_luauml_output_hook:n

```

At the end of the document we must finish and close the file:

```

254 \AddToHook{enddocument/afterlastpage}
255 {
256     \iow_now:Ne \g__math_luauml_iow
257     { \c__math_mathml_write_final_tl }
258     \iow_close:N \g__math_luauml_iow
259 }
260 \msg_note:nnnn { tag }
261 { luauml-status }{ enabled }{ create }
262 }
263 }

```

`\UseMathForPositioningText`

The `\UseMathForPositioningText` command indicates that a directly following `$` is not a real math formula, but that the math mode is only entered to position ordinary text with the help of built in T_EX algorithms normally used for math, e.g., `\vcenter`, super and subscripts.

Signalling that special usage is necessary in the case tagged PDF is produced, because then such math mode should not generate a “formula” structure.

The command requires that it is immediately followed by `$`; anything else will result in a low-level T_EX error. As it is not a user but a developer command, this seems acceptable for the sake of fast runtime execution.

The way it is implemented it can be used in legacy code in front of any `$` that switches to math mode for non-math purposes. If tagging is active it will ensure that this particular math mode content is not treated as math with respect to tagging (though nested math still is). If tagging is inactive the command is simply ignored.

Starting with L^AT_EX 2026-06-01 it is not longer used by the kernel as math is not longer used in tabular and super and subscripts.

```

264 \cs_set_protected:Npn \UseMathForPositioningText $ {

```

Before the math mode is started we ensure that its content is not collected by the grabber.

```

265 \bool_if:NTF \l__math_collected_bool
266 { $ }
267 {
268   \bool_set_true:N \l__math_collected_bool
269   $

```

Once inside math mode we reenable grabbing, so that any nested math (within text) is grabbed.

```

270   \bool_set_false:N \l__math_collected_bool

```

In addition we decrement the math level (which was automatically incremented when entering math mode) so that this math mode is transparent in `\__math_luamml_activate_write:.`

```

271   \int_decr:N \@math@level
272   }
273 }

```

(End of definition for `\UseMathForPositioningText`. This function is documented on page ??.)

And now keys to activate/deactivate luamml feature

`\g__math_luamml_load_tl` This variable will be used to suppress the loading of luamml altogether.

```

274 \tl_new:N \g__math_luamml_load_tl
275 \tl_gset:Nn \g__math_luamml_load_tl {}

```

`\g__math_luamml_write_bool` This variable decides if luamml writes a mathml altogether.

```

276 \bool_new:N \g__math_luamml_write_bool
277 \bool_gset_true:N \g__math_luamml_write_bool

```

`\__math_luamml_ignore:` Internal variants of the luamml commands, that can be remapped if needed.

```

\__math_luamml_structelem:
278 \cs_new:Npn \__math_luamml_structelem: {}
279 \cs_new:Npn \__math_luamml_ignore: {}

```

(End of definition for `\__math_luamml_ignore:` and `\__math_luamml_structelem:.`)

```

280 \msg_new:nnn { tag }{ PDF-2.0-recommended }
281 {
282   The~key~#1~will~not~work~properly~with~PDF~#2.\\
283   Switching~to~PDF~2.0~is~recommended.
284 }
285 \keys_define:nn { __tag / setup }
286 {

```

At first a key to suppress the loading altogether

```

287   math/mathml/luamml/load .choice: ,
288   math/mathml/luamml/load/true .code:n = {\tl_gset:Nn \g__math_luamml_load_tl{1}},
289   math/mathml/luamml/load/false .code:n = {\tl_gset:Nn \g__math_luamml_load_tl{-
290   1}},
291   math/mathml/luamml/load .default:n = true,
292   math/mathml/luamml/load .usage:n=preamble,

```

A key to activate math structure elements.

```

292     math/mathml/structelem .choice:,
293     math/mathml/structelem/true .code:n =
294     {
295         \pdf_version_compare:NnT < {2.0}
296         {
297             \msg_warning:nnne { tag }{ PDF-2.0-recommended }
298             { math/mathml/structelem }{ \pdf_version: }
299         }
300         \cs_set:Npn\__math_luaamml_structelem:{\luaamml_structelem:}
301         \cs_set:Npn\__math_luaamml_ignore:{\luaamml_ignore:}
302         \sys_if_engine luatex:T {
303             \bool_set_true:N \l__math_math_content_artifact_bool
304         }
305     },
306     math/mathml/structelem/false .code:n =
307     {
308         \cs_set_eq:NN\__math_luaamml_structelem:\prg_do_nothing:
309         \cs_set_eq:NN\__math_luaamml_ignore:\prg_do_nothing:
310         \bool_set_false:N \l__math_math_content_artifact_bool
311     },
312     math/mathml/structelem .default:n = true,

```

and a key to call the ignore flag. This should only be used locally.

```

313     math/mathml/ignore .code:n = {\luaamml_ignore:},
314
315     math/mathml/luamml/write .choice:,
316     math/mathml/luamml/write/true .code:n =
317     {
318         \tl_gset:Nn \g__math_luaamml_load_tl{1}
319         \bool_gset_true:N \g__math_luaamml_write_bool
320     },
321     math/mathml/luamml/write/false .code:n =
322     {
323         \bool_gset_false:N \g__math_luaamml_write_bool
324     },
325     math/mathml/luamml/write .default:n = true,
326     math/mathml/luamml/write .usage:n=preamble,

```

alias keys for compatibility

```

326     math/mathml/luamml .bool_gset:N = \g__math_luaamml_write_bool,
327     math/mathml/luamml .usage:n=preamble
328 }

```

`math/mathml/write` (*tag socket*) This writes a html-dummy with the hash and the math content. This should be optional, so it uses a socket that can be disabled

```

329 \NewTaggingSocket{math/mathml/write}{0}

```

On (*plug*)

```

330 \NewTaggingSocketPlug{math/mathml/write}{0n}
331 {
332     \iow_now:Ne \g__math_writedummy_iow
333     {
334         \l__math_mathml_write_before_tl

```

```

335     <math~ xmlns="http://www.w3.org/1998/Math/MathML"></math>
336     \c__math_mathml_write_after_tl
337   }
338 }

```

And now a key to activate the socket.

```

339 \keys_define:nn { __tag / setup }
340 {
341   math/mathml/write-dummy .code:n =
342   {
343     \bool_gset_true:N \g__tag_math_mathml_AF_bool
344     \tl_if_exist:NF\g__math_writedummy_iow
345     {
346       \iow_new:N \g__math_writedummy_iow
347       \iow_open:Nn \g__math_writedummy_iow
348       {
349         \c_sys_jobname_str-mathml-dummy.html
350       }
351       \iow_now:Ne \g__math_writedummy_iow
352       {
353         \c__math_mathml_write_init_tl
354       }
355       \AssignTaggingSocketPlug{math/mathml/write/prepare}{On}
356       \AssignTaggingSocketPlug{math/mathml/write}{On}
357       \AddToHook{enddocument/afterlastpage}
358       {
359         \iow_now:Ne \g__math_writedummy_iow
360         { \c__math_mathml_write_final_tl }
361         \iow_close:N \g__math_writedummy_iow
362       }
363     }
364   },
365   math/mathml/write-dummy .usage:n=preamble
366 }

```

_math_AF_process_mathml_files:

```

367 \box_new:N\l__math_tmpa_box
368 \cs_new_protected:Npn \_math_AF_process_mathml_files:
369 {
370   \hbox_set:Nn \l__math_tmpa_box
371   {
372     \pdfdict_put:nnn { l_pdffile/Filespec }{AFRelationship} { /Supplement }
373     \pdfdict_put:nne
374     { l_pdffile }{Subtype}
375     { \pdf_name_from_unicode_e:n{application/mathml+xml} }
376     \char_set_catcode_other:N \#
377     \cs_set_eq:NN\mml \_math_AF_html_reader:w
378     \clist_map_inline:Nn \l__tag_math_mathml_files_clist
379     {
380       \file_if_exist:nTF {##1.html}
381       {
382         \typeout{Info:~reading~mathml~file~##1}
383         \file_input:n {##1.html}
384         \bool_gset_true:N\g__tag_math_mathml_AF_bool

```

```

385         }
386         {
387             \typeout{Info:~mathml~file~##1~does~not~exist}%info message
388         }
389     }
390 }
391 \box_clear:N \l__math_tmpa_box
392 \bool_if:NT\g__tag_math_mathml_AF_bool
393 {
394     \typeout{Info:~Activating~mathml~support}
395     \AssignTaggingSocketPlug{math/struct/begin}{mathml-AF}
396     \AssignTaggingSocketPlug{math/struct/end}{mathml-AF}
397     \AddToHook{enddocument/info}
398     {
399         \iow_term:n{MathML~statistic}
400         \iow_term:n{=====}
401         \iow_term:e{==>~\int_use:N\g__math_mathml_total_int\c_space_tl
402         MathML~fragments~read}
403         \iow_term:e{==>~\int_use:N\g__math_mathml_int\c_space_tl
404         different~MathML~fragments}
405         \iow_term:e{==>~\int_use:N\g__math_math_total_int\c_space_tl
406         math~fragments~found}
407         \iow_term:e{==>~\int_use:N\g__math_mathml_AF_found_int\c_space_tl
408         fitting~MathML~AF~found}
409         \iow_term:e{==>~\int_use:N\g__math_mathml_AF_attached_int\c_space_tl
410         MathML~AF~attached}
411     }
412 }
413 }
414 \AddToHook{begindocument}{\__math_AF_process_mathml_files:}

```

(End of definition for `\__math_AF_process_mathml_files:.`)

8.7 Mathstyle detection

In some cases we need to detect the mathstyle used in a `\mathchoice` command and to disable/enable tagging in the unused branches. This is currently only used in the `amstext` command `\text` but is perhaps also needed in other cases, so we create a general command.

```

\l__math_mathstyle_int
\g__math_mathchoice_int
mathstyle
415 \int_new:N \l__math_mathstyle_int
416 \int_new:N \g__math_mathchoice_int
417 \property_new:nnnn{mathstyle}{now}{-1}{\int_use:N \l__math_mathstyle_int }

```

(End of definition for `\l__math_mathstyle_int`, `\g__math_mathchoice_int`, and `mathstyle`.)

For now internal, but perhaps will need a public version. The command should be used in every branch of a `\mathchoice` (with the correct mathstyle number) and with an unique label (which should be the same in every branch). `\g__math_mathchoice_int` can be, e.g., increased before the mathchoice and then used.

```

\__math_tag_if_mathstyle:nn
418 \cs_new_protected:Npn \__math_tag_if_mathstyle:nn #1 #2

```

```

419 %\#1 refers to label
420 %\#2 is a number for the mathstyle (typically 0,2,4,6)
421 {
422   \int_set:Nn \l__math_mathstyle_int {#2}
423   \property_record:nn {#1} { mathstyle }
424   \int_compare:nNnTF { \property_ref:nn {#1}{ mathstyle} } = { #2 }
425     { \tag_resume:n{\mathchoice} }{ \tag_suspend:n{\mathchoice} }
426 }
427 \cs_generate_variant:Nn \__math_tag_if_mathstyle:nn {en}

```

(End of definition for `\__math_tag_if_mathstyle:nn`.)

8.8 Tagging options

```

428 \keys_define:nn { __tag / setup }
429 {
430   math/mathml/sources .clist_set:N = \l__tag_math_mathml_files_clist,
431   math/alt/use         .bool_set:N = \l__tag_math_alt_bool,
432   math/MS/use          .bool_set:N = \l__tag_math_MSFT_bool,
433   viewer/pane/mathml   .bool_set:N = \l__tag_math_mathml_pane_bool,
434   viewer/pane/mathml   .initial:n = true,
435   viewer/pane/mathsource .bool_set:N = \l__tag_math_texsource_pane_bool,
436   math/mathml/AF .bool_set:N = \l__tag_math_mathml_AF_bool,
437   math/mathml/AF .initial:n = true,
438   math/tex/AF .bool_set:N = \l__tag_math_texsource_AF_bool,
439   math/tex/AF .initial:n = true
440 }

```

alt is required for pdf/UA-1. TODO: l3pdfmeta should support this test.

```

441 \AddToHook{begindocument/end}
442 {
443   \str_if_eq:eeT
444     {1}
445     {
446       \exp_last_unbraced:Ne\use_i:nn
447         {\GetDocumentProperty{document/pdfstandard-UA}}
448       \c_empty_tl\c_empty_tl
449     }
450     {
451       \bool_if:NF \l__tag_math_alt_bool
452       {
453         \typeout{PDF/UA-1~detected.~Enabling~alt~text~on~Formula}
454       }
455       \bool_set_true:N\l__tag_math_alt_bool
456     }
457 }

```

8.8.1 Meta keys

The `math/setup` key accepts a list with the values `mathml-SE`, `mathml-AF` and `tex-AF`. It is a fast way to set the main option. It at first disables them all, to get a clean state.

```

458 \keys_define:nn {__tag / setup}
459 {
460   math/setup .code:n =

```

```

461 {
462   %deactivate loading of luamml
463   \tl_gset:Nn \g__math_luamml_load_tl{-1}
464   \keys_set:nn {__tag / setup}
465   {
466     %deactivate tex source AF
467     math/tex/AF = false,
468     %deactivate reading of mathml-AF
469     math/mathml/sources=,
470     math/mathml/AF=false,
471     %deactivate structelem
472     math/mathml/structelem=false,
473     %handle value
474   }
475   \clist_map_inline:nn { #1}
476   {
477     \keys_set:nn {__tag / setup}{math/__setup/##1}
478   }
479 },
480 math/__setup / mathml-SE .code:n =
481 {
482   \tl_gset:Nn \g__math_luamml_load_tl{1}
483   \keys_set:nn {__tag / setup}
484   {
485     math/mathml/structelem=true
486   }
487 },
488 math/__setup / mathml-AF .code:n =
489 {
490   \tl_gset:Nn \g__math_luamml_load_tl{1}
491   \clist_put_right:Ne\l__tag_math_mathml_files_clist
492   {\c_sys_jobname_str-mathml,\c_sys_jobname_str-luamml-mathml}
493   \keys_set:nn {__tag / setup}
494   {
495     math/mathml/AF=true
496   }
497 },
498 math/__setup / mathml-MS .code:n =
499 {
500   \tl_gset:Nn \g__math_luamml_load_tl{1}
501   \cs_set_eq:NN\__math_MSFT_mml:nn\__math_MSFT_mml_aux:nn
502   \bool_set_true:N\l__tag_math_MSFT_bool
503   \clist_put_right:Ne\l__tag_math_mathml_files_clist
504   {\c_sys_jobname_str-mathml,\c_sys_jobname_str-luamml-mathml}
505 },
506 math/__setup / tex-AF .code:n =
507 {
508   \keys_set:nn {__tag / setup}
509   {
510     math/tex/AF =true
511   }
512 },
513 }

```

8.9 Sockets

8.9.1 Main inline math sockets

`math/inline/begin` (*tag socket*) These sockets are already declared in `ltagging` and only documented here. The first two sockets are meant to embed inline math into the surrounding (so to close/reopen, e.g., MC-chunks). The other two implement the actual formula structure. The formula sockets are despite their naming not symmetric: the begin socket is issued after the math has started, while the end socket is after the math!

```
514 %\NewTaggingSocket{math/inline/begin}{0}
515 %\NewTaggingSocket{math/inline/end}{0}
516 %\NewTaggingSocket{math/inline/formula/begin}{2} %
517 %\NewTaggingSocket{math/inline/formula/end}{0}
```

MC (*plug*)

```
518 \NewTaggingSocketPlug
519   {math/inline/begin}
520   {MC}
521   {\tag_mc_end_push:}
522 \NewTaggingSocketPlug
523   {math/inline/end}
524   {MC}
525   {\tag_mc_begin_pop:n{}}
```

We probably will want to test different tagging recipes.

default (*plug*)

```
526 \NewTaggingSocketPlug
527   {math/inline/formula/begin}
528   {default}

529 { \tagpdfparaOff
530   \__math_lua_mml_structelem:
531   \tag_socket_use:n{math/content}
532   \tag_socket_use:n{math/struct/begin}
533   #2
534   \tag_socket_use:n{math/end}
535 }
536 \NewTaggingSocketPlug
537   {math/inline/formula/end}
538   {default}
539 {
540   \tag_socket_use:n{math/struct/end}
541 }
```

8.9.2 Main display math sockets

`math/display/begin` (*tag socket*) These sockets are already declared in `ltagging` and only documented here. The first two sockets are meant to embed display math into the surrounding (so to close/reopen, e.g., MC-chunks and P-structure). The other two implement the actual formula structure. The formula sockets are despite their naming not symmetric: the begin socket is issued after the math has started, while the end socket is after the math!

```
542 %\NewTaggingSocket{math/display/begin}{0}
```

```

543 %\NewTaggingSocket{math/display/end}{0}
544 %\NewTaggingSocket{math/display/formula/begin}{2} %
545 %\NewTaggingSocket{math/display/formula/end}{0}

```

default (*plug*)

```

546 \NewTaggingSocketPlug
547 {math/display/begin}
548 {default}
549 {
550   \UseTaggingSocket{para/textblock/end}
551 }
552 \NewTaggingSocketPlug
553 {math/display/end}
554 {default}
555 {
556 }

```

default (*plug*)

```

557 \NewTaggingSocketPlug
558 {math/display/formula/begin}
559 {default}
560 {
561   \tagpdfparaOff
562   \__math_luauml_structelem:
563   \tag_socket_use:n{math/content}
564   \tag_socket_use:n{math/struct/begin}
565   #2
566   \tag_socket_use:n{math/end}
567 }
568 \NewTaggingSocketPlug
569 {math/display/formula/end}
570 {default}
571 {
572   \tag_socket_use:n{math/struct/end}
573 }

```

8.9.3 Sockets plugs for tags (labels)

$$\tag{tag socket}$$
 These sockets are already declared in ltagging and only documented here. These sockets are used in `\maketag__math@` to tag labels as Lbl. luamml changes the plug to move the Lbl into the math structure with an intent.

```

574 %\NewTaggingSocket{math/display/tag/begin}{0}
575 %\NewTaggingSocket{math/display/tag/end}{0}

```

default (*plug*)

```

576 \NewTaggingSocketPlug
577 {math/display/tag/begin}
578 {default}
579 {
580   \tag_mc_end:
581   \tag_struct_begin:n {tag=\UseStructureName{math/label}}
582   \tag_mc_begin:n {}
583 }

```

```

584 \NewTaggingSocketPlug
585   {math/display/tag/end}
586   {default}
587   {
588     \tag_mc_end:
589     \tag_struct_end:
590     \tag_mc_begin:n{ }
591   }
592 \AssignTaggingSocketPlug{math/display/tag/begin}{default}
593 \AssignTaggingSocketPlug{math/display/tag/end}{default}

```

8.9.4 Internal sockets

`\l__math_content_template_tl`

The default text used as alt or actual text.

```

594 \tl_new:N\l__math_content_template_tl
595 \tl_set:Nn \l__math_content_template_tl
596   {
597     LaTeX~ formula~ starts~
598     \exp_not:N\begin{\g__math_grabbed_env_tl}
599     \c_space_tl
600     \exp_not:V\g__math_grabbed_math_tl
601     \c_space_tl
602     \exp_not:N\end{\g__math_grabbed_env_tl}
603     \c_space_tl LaTeX~ formula~ ends~
604   }

```

`\l__math_texsource_template_tl`

The default text used as texsource

```

605 \tl_new:N\l__math_texsource_template_tl
606 \tl_const:Nn\c__math_inline_env_tl {math}
607 \tl_set:Nn \l__math_texsource_template_tl
608   {
609     \tl_if_eq:NNTF\g__math_grabbed_env_tl\c__math_inline_env_tl
610     {
611       $
612       \exp_not:V\g__math_grabbed_math_tl
613       $
614     }
615     {
616       \exp_not:N\begin{\g__math_grabbed_env_tl}
617       \exp_not:V\g__math_grabbed_math_tl
618       \exp_not:N\end{\g__math_grabbed_env_tl}
619     }
620   }

```

math/content (*tag socket*) The math content is stored in associated files and used for actual and alternative text. As the exact text is still unclear we use a socket to be able to test variants. The socket

should set all four `tl` vars above, if needed to identical values. It can use the two variables `\g__math_grabbed_env_tl` and `\g__math_grabbed_math_tl`

```
621 \NewTaggingSocket{math/content}{0}
```

Some default sockets to set the contents. TODO: think about naming convention. TODO: think how this should organized so that one has options to change from the outside and so that there are less repetitions.

`actual+source (plug)`

```
622 \NewTaggingSocketPlug
623   {math/content}
624   {actual+source}
625   {
626     \tl_set:N\l__math_content_actual_tl
627     {
628       \l__math_content_template_tl
629     }
630     \tl_set:N\l__math_content_AF_source_tl
631     {
632       \l__math_texsource_template_tl
633     }
634     \tl_set:Nn \l__math_content_AF_mathml_tl {}
635     \tl_set:Nn \l__math_content_alt_tl {}
636   }
```

`alt+source (plug)`

```
637 \NewTaggingSocketPlug
638   {math/content}
639   {alt+source}
640   {
641     \tl_set:N\l__math_content_alt_tl
642     {
643       \l__math_content_template_tl
644     }
645     \tl_set:N\l__math_content_AF_source_tl
646     {
647       \l__math_texsource_template_tl
648     }
649     \tl_set:Nn \l__math_content_AF_mathml_tl {}
650     \tl_set:Nn \l__math_content_actual_tl {}
651   }
```

```
652 \AssignTaggingSocketPlug{math/content}{alt+source}
```

`math/struct/begin (tag socket)` For the main structure we use a socket too. This allows, e.g., to create a special one
`math/struct/end (tag socket)` for `luamml` which setups additional objects. The `begin` socket can use the two variables `\g__math_grabbed_env_tl` and `\g__math_grabbed_math_tl`

```
653 \NewTaggingSocket{math/struct/begin}{0}
654 \NewTaggingSocket{math/struct/end}{0}
```

`default (plug)` TODO: think about some naming convention ...

```
655 \NewTaggingSocketPlug
656   {math/struct/begin}
```

```

657 {default}
658 {
659   \bool_if:NTF\l__tag_math_texsource_AF_bool
660   { \tl_set_eq:NN \l__math_content_AF_source_tmpa_tl \l__math_content_AF_source_tl }
661   { \tl_clear:N \l__math_content_AF_source_tmpa_tl }
662   \tl_if_eq:NnTF\g__math_grabbed_env_tl {math}
663   {
664     \tl_set:Nn\l__math_attribute_class_tl{inline}
665   }
666   {
667     \tl_set:Nn\l__math_attribute_class_tl{display}
668   }
669   \bool_if:NF\l__tag_math_alt_bool
670   { \tl_set:Nn \l__math_content_alt_tl{} }
671   \tag_struct_begin:n
672   {
673     tag=\UseStructureName{math/\l__math_attribute_class_tl},
674     attribute-class=\l__math_attribute_class_tl,
675     texsource      = \l__math_content_AF_source_tmpa_tl,
676     title-o        = \g__math_grabbed_env_tl,
677     actualtext     = \l__math_content_actual_tl,
678     alt            = \l__math_content_alt_tl
679   }
680
681   \__math_debug_typeout:n{grabbed-math=\meaning\g__math_grabbed_math_tl}
682   \bool_if:NTF \l__math_math_content_artifact_bool
683   {
684     \tag_mc_begin:n{ artifact }
685   } {
686     \tag_mc_begin:n{}
687   }
688   \NewTaggingSocketPlug
689   {math/struct/end}
690   {default}
691   { \tag_mc_end: \tag_struct_end: }
692
693   \AssignTaggingSocketPlug{math/struct/begin}{default}
694   \AssignTaggingSocketPlug{math/struct/end}{default}

```

mathml-AF (plug) This socket tries to add a mathml-AF to formula. It is activated if a mathml.html has been found and loaded. As it disturbs the reading of the AF it currently deactivates the /Alt key, unless it has been reenabled with `math/alt/use=true`

```

695 \cs_generate_variant:Nn \str_mdfive_hash:n {o}
696 \tl_new:N\l__math_content_hash_tl

```

we need to save the grabbed math:

```

697 \tl_new:N\l__math_grabbed_math_tl

```

the socket definition

```

698 \NewTaggingSocketPlug
699 {math/struct/begin}
700 {mathml-AF}
701 {

```

```

702 \int_gincr:N\g__math_math_total_int
703 \tl_set:N\l__math_content_hash_tl
704   {\str_mdfive_hash:o { \l__math_content_AF_source_tl }}
705 \tl_set_eq:NN\l__math_grabbed_math_tl\g__math_grabbed_math_tl
706 \tl_if_eq:NnTF\g__math_grabbed_env_tl {math}
707   {
708     \tl_set:Nn\l__math_attribute_class_tl{inline}
709   }
710   {
711     \tl_set:Nn\l__math_attribute_class_tl{display}
712   }
713 \bool_if:NF\l__tag_math_alt_bool
714   { \tl_set:Nn \l__math_content_alt_tl{} }

```

debugging option. TODO: hide in debug key.

```

715 \tl_if_exist:cTF { g__math_mathml_ \l__math_content_hash_tl _tl }
716   {
717     \int_gincr:N\g__math_mathml_AF_found_int
718     \bool_if:NTF \l__tag_math_mathml_AF_bool
719     {
720       \int_gincr:N\g__math_mathml_AF_attached_int
721
722       \__math_debug_typeout:n {Inserting~mathml~with~Hash~\l__math_content_hash_tl}
723     }
724     \__math_debug_typeout:n {Ignoring~mathml~with~Hash~\l__math_content_hash_tl}
725   }
726   {
727     \bool_if:NT \l__tag_math_mathml_AF_bool
728     {
729       \typeout {WARNING:~mathml~missing~for~hash~\l__math_content_hash_tl}
730     }
731   }
732   {
733     \tag_socket_use:n {math/mathml/write/prepare}
734     \tag_socket_use:n {math/mathml/write} % write hash if request
735     \bool_if:NTF\l__tag_math_texsource_AF_bool
736     { \tl_set_eq:NN \l__math_content_AF_source_tmpa_tl \l__math_content_AF_source_tl }
737     { \tl_clear:N \l__math_content_AF_source_tmpa_tl }
738     \tag_struct_begin:n
739     {
740       tag=\UseStructureName{math/\l__math_attribute_class_tl},
741       attribute-class=\l__math_attribute_class_tl, %
742       attribute =
743       \bool_if:NT \l__tag_math_MSFT_bool
744       {
745         \cs_if_exist_use:c {g__math_mathml_MSFT_ \l__math_content_hash_tl _tl}
746       },
747       AFref =
748       \bool_if:NT\l__tag_math_mathml_AF_bool
749       {
750         \cs_if_exist_use:c {g__math_mathml_ \l__math_content_hash_tl _tl}
751       },
752       texsource = \l__math_content_AF_source_tmpa_tl, % should be after mathml AF!

```

```

753     title-o      = \g__math_grabbed_env_tl,      %
754     alt          = \l__math_content_alt_tl
755   }
756   \__math_debug_typeout:n {grabbed~math=\meaning\g__math_grabbed_math_tl}
757   \tag_mc_begin:n{ }
758 }

```

not really needed but looks more symmetric:

```

759 \NewTaggingSocketPlug
760 {math/struct/end}
761 {mathml-AF}
762 {
763   \tag_mc_end:
764   \tag_struct_end:
765 }

```

math/end (*tag socket*) A socket used at the end of the math (before the closing dollar(s)) which can, e.g., set a flag for luamml.

```

766 \NewTaggingSocket{math/end}{0}

767 \AssignTaggingSocketPlug{math/inline/begin}{MC}
768 \AssignTaggingSocketPlug{math/inline/end}{MC}
769 \AssignTaggingSocketPlug{math/inline/formula/begin}{default}
770 \AssignTaggingSocketPlug{math/inline/formula/end}{default}
771 \AssignTaggingSocketPlug{math/display/begin}{default}
772 \AssignTaggingSocketPlug{math/display/end}{default}
773 \AssignTaggingSocketPlug{math/display/formula/begin}{default}
774 \AssignTaggingSocketPlug{math/display/formula/end}{default}

```

8.10 Interface commands

```

\__math_process:nn A no-op place-holder; the internal wrapper means that it does not need to be concerned
\__math_process:Vn with internals.
\__math_process_auxi:nn
\__math_process_auxii:nn
775 \newif\ifmeasuring@
776 \cs_new_protected:Npn \__math_process:nn #1#2
777 {
778   \legacy_if:nF { measuring@ }
779   {
780     \tl_if_in:nnTF {#2} { \m@th }
781     { \bool_set_true:N\l__math_fakemath_bool }
782     { \tl_trim_spaces_apply:nN {#2} \__math_process_auxi:nn {#1} }
783   }
784 }
785 \cs_generate_variant:Nn \__math_process:nn { V }
786 \cs_new_protected:Npn \__math_process_auxi:nn #1#2
787 {
788   \tl_gset:Nn \g__math_grabbed_env_tl {#2}
789   \tl_gset:Nn \g__math_grabbed_math_tl {#1}
790   \__math_process_auxii:nn {#2} {#1}
791 }
792 \cs_new_protected:Npn \__math_process_auxii:nn #1#2 { }

```

(End of definition for `\__math_process:nn`, `\__math_process_auxi:nn`, and `\__math_process_auxii:nn`.)

```
\math_processor:n A simple installer
793 \cs_new_protected:Npn \math_processor:n #1
794 { \cs_set_protected:Npn \__math_process_auxii:nn ##1##2 {#1} }
(End of definition for \math_processor:n. This function is documented on page 5.)
```

8.11 Content grabbing

```
\MathCollectTrue
\MathCollectFalse
795 \cs_set_protected:Npn \MathCollectTrue{\bool_set_false:N \l__math_collected_bool}
796 \cs_set_protected:Npn \MathCollectFalse{\bool_set_true:N \l__math_collected_bool}
(End of definition for \MathCollectTrue and \MathCollectFalse. These functions are documented on
page 6.)
```

```
\__math_grab_dollar:w Top-level function to handle grabbing of inline math mode delimited by $ tokens. We
\__math_grab:n provide two different ways to do that: a token-by-token one that can be used everywhere,
and a fast delimited one that does not work anywhere that the end $ token may be hidden,
most obviously in tabulars. The function here is therefore set up as a variable starting
point.
```

```
797 \cs_new_protected:Npn \__math_grab_dollar:w { \__math_grab_dollar_delim:w }
```

After grabbing inline math material, there is again common processing independent of mechanism of collection.

```
798 \cs_new_protected:Npn \__math_grab:n #1
799 {
```

We need to do processing first as this picks up “fake” math mode: that information is needed below. The captured material *could* contain & tokens, so we ensure that these do no cause an issue if we are inside an \halign.

```
800 \group_align_safe_begin:
801 \__math_process:nn { math } {#1}
802 \group_align_safe_end:
```

We do not want math tagging in fakemath or when measuring, We also do not want math tagging if tagging has been suspended.

```
803 \bool_lazy_any:nTF
804 {
805   {\legacy_if_p:n { measuring@ }}
806   { \l__math_fakemath_bool }
807   { \tl_if_blank_p:n {#1} }
808 }
809 {
810   \__math_luamml_ignore:
811   #1 $ % $
812 }
813 {
814   \tag_socket_use:n {math/inline/begin} %end P-MC
```

We do no use a tagging socket here, so that the argument (the math) is not lost, tagging-project issue 661.

```
815 \tag_socket_use:nnn {math/inline/formula/begin}{-}{#1}
816 $ % $
817 \tag_socket_use:n {math/inline/formula/end}
```

```

818         \tag_socket_use:n {math/inline/end} % restart P-MC
819     }
820 }

```

(End of definition for __math_grab_dollar:w and __math_grab:n.)

__math_grab_dollar_delim:w Grab up to a single \$, for inline math mode, suppressing any processing if the token is \m@th found in the content.

```

821 \cs_new_protected:Npn \__math_grab_dollar_delim:w #1 $ % $
822 { \__math_grab:n {#1} }

```

(End of definition for __math_grab_dollar_delim:w.)

__math_grab_dollardollar:w And for the classical T_EX display structure.

```

823 \cs_new_protected:Npn \__math_grab_dollardollar:w #1 $$ {
824     \tl_if_blank:nF {#1}
825     {
826         \__math_process:nn { equation* } {#1}
827         \tag_socket_use:n {math/display/begin}
828         \tag_socket_use:nn{math/display/formula/begin}-{#1}
829     }

```

Prepare to finish the display math formula and let T_EX do its job; then regain control after the formula has been contributed to the page, in order to add the tagging followed by the correct penalty and skip.

```

830     \__math_prepare_display_end:
831     $$
832 }

```

(End of definition for __math_grab_dollardollar:w.)

__math_grab_inline_delim:w Collect inline math content and deal with the need to move to math mode.

```

833 \cs_new_protected:Npn \__math_grab_inline_delim:w % \ (
834     #1 \)
835     {
836         \tl_if_blank:nF {#1}
837         {
838             $ #1 $
839         }
840         \bool_set_false:N \l__math_collected_bool
841     }

```

(End of definition for __math_grab_inline_delim:w.)

__math_grab_inline:w See \@@_grab_dollar:w.

```

842 \cs_new_protected:Npn \__math_grab_inline:w { \__math_grab_inline_delim:w }

```

(End of definition for __math_grab_inline:w.)

__math_grab_eqn:w For the most common use of \[/\]: turn into an environment.

```

843 \cs_new_protected:Npn \__math_grab_eqn:w % \[
844     #1 \]
845     {
846         % \typeout{collected? = \bool_if:NTF \l__math_collected_bool {true}{false}}
847         \begin { equation* } #1 \end { equation* }
848     }

```

(End of definition for __math_grab_eqn:w.)

8.12 Token-by-token inline grabbing

Grabbing inline math token-by-token is more involved. The mechanism here is essentially a simplified version of that originally seen in `collcell` and refined in `siunitx`. We make use of the fact that in math mode spaces are ignored, so we have to deal with only N-type tokens and groups. Furthermore, there is no need to look inside groups, so the only special cases are a small selection of N-type tokens.

`\l__math_grabbed_tl` For collection of the material piecewise.

```
849 \tl_new:N \l__math_grabbed_tl
```

`\l__math_grab_env_int` Needed to count up the number of nested environments encountered.

```
850 \int_new:N \l__math_grab_env_int
```

`\__math_grab_loop_init:` The lead-off here establishes a group: we need that as we will have to be careful in the way `\cr` is handled and ensure this is only manipulated whilst grabbing. The main loop is then started.

```
851 \cs_new_protected:Npn \__math_grab_loop_init:
852 {
853   \group_begin:
854   \tl_clear:N \l__math_grabbed_tl
855   \__math_grab_loop:
856 }
857 \cs_new_protected:Npn \__math_grab_loop:
858 {
859   \peek_remove_spaces:n
860   {
861     \peek_meaning:NTF \c_group_begin_token
862     { \__math_grab_loop_group:n }
863     { \__math_grab_loop_token:N }
864   }
865 }
```

(End of definition for `\__math_grab_loop_init:` and `\__math_grab_loop:`.)

`\__math_grab_loop_group:n` Handling of grabbed groups is pretty easy.

```
\__math_grab_loop_store:n
866 \cs_new_protected:Npn \__math_grab_loop_group:n #1
867 { \__math_grab_loop_store:n { {#1} } }
868 \cs_new_protected:Npn \__math_grab_loop_store:n #1
869 {
870   \tl_put_right:Nn \l__math_grabbed_tl {#1}
871   \__math_grab_loop:
872 }
```

(End of definition for `\__math_grab_loop_group:n` and `\__math_grab_loop_store:n`.)

`\__math_grab_loop_token:N` Filter out the special cases: for performance reasons, use a hash table approach rather than a loop (*cf.* `collcell`). To handle the case of a nested array or similar, an alignment safe group is added around the first occurrence of a nested environment.

```
\__math_grab_loop_$:
\__math_grab_loop_\:
\__math_grab_loop_\begin:
\__math_grab_loop_\end:
\__math_grab_loop_\ignorespaces:
\__math_grab_loop_\unskip:
\__math_grab_loop_\textonly@unskip:
\__math_grab_loop_\end:n
873 \cs_new_protected:Npn \__math_grab_loop_token:N #1
```

```

874 {
875   \cs_if_exist_use:cF
876     { __math_grab_loop_ \token_to_str:N #1 : }
877     { \__math_grab_loop_store:n {#1} }
878 }
879 \cs_new_protected:cpn { __math_grab_loop_ \token_to_str:N $ : }
880 { \__math_grab_loop_end: }
881 \cs_new_protected:cpn { __math_grab_loop_ \token_to_str:N \) : }
882 { \__math_grab_loop_end: }
883 \cs_new_protected:cpn { __math_grab_loop_ \token_to_str:N \\ : }
884 {
885   \int_compare:nNnTF \l__math_grab_env_int = 0
886     { \__math_grab_loop_newline: }
887     { \__math_grab_loop_store:n { \\ } }
888 }

```

In contrast to `colcell`, nesting is tracked by counting `\begin/\end` pairs: this is needed in case there is a tabular-like construct containing `\\` inside a cell. As a result, the end-of-tabular can be detected without checking the name argument: if `\end` is encountered at nesting level 0, we've hit the end of a cell. In that case, end the row and leave the environment to clean up.

```

889 \cs_new_protected:cpn { __math_grab_loop_ \token_to_str:N \begin : }
890 {
891   \int_incr:N \l__math_grab_env_int
892   \int_compare:nNnT \l__math_grab_env_int = 1
893     { \group_align_safe_begin: }
894   \__math_grab_loop_store:n { \begin }
895 }
896 \cs_new_protected:cpe { __math_grab_loop_ \token_to_str:N \end : }
897 {
898   \exp_not:N \int_compare:nNnTF \exp_not:N \l__math_grab_env_int = 0
899     {
900       \exp_not:N \__math_grab_loop_newline:
901       \exp_not:N \end
902     }
903     { \exp_not:c { __math_grab_loop_ \token_to_str:N \end :n } }
904 }
905 \cs_new_protected:cpn { __math_grab_loop_ \token_to_str:N \end :n } #1
906 {
907   \int_decr:N \l__math_grab_env_int
908   \tl_put_right:Nn \l__math_grabbed_tl { \end {#1} }
909   \int_compare:nNnT \l__math_grab_env_int = 0
910     { \group_align_safe_end: }
911   \__math_grab_loop:
912 }
913 \tl_map_inline:nn { \ignorespaces \unskip \textonly@unskip }
914 {
915   \cs_new_protected:cpn { __math_grab_loop_ \token_to_str:N #1 : }
916   { \__math_grab_loop: }
917 }

```

(End of definition for `\__math_grab_loop_token:N` and others.)

`\__math_grab_loop_newline:` To allow collection of tokens in the part of the `\halign` template after `#`, we need `TEX` to see the primitive with the loop token in the right place. That is done by re-defining `\cr`

at present. Ideally there would be a socket in the definition of `tabular`, etc., to handle this: there is also the need to examine in interaction with `longtable`, which also redefines `\cr`.

```

918 \cs_new_protected:Npn \__math_grab_loop_newline:
919 {
920   \if_false: { \fi:
921     \cs_set_protected:Npn \cr
922     {
923       \__math_grab_loop:
924       \tex_cr:D
925     }
926   \if_false: } \fi:
927   \\\
928 }

```

(End of definition for `\__math_grab_loop_newline:.`)

`\__math_grab_loop_end:` Clean up and pass on.

```

929 \cs_new_protected:Npn \__math_grab_loop_end:
930 {
931   \exp_args:NNV \group_end:
932   \__math_grab:n \l__math_grabbed_tl
933 }

```

(End of definition for `\__math_grab_loop_end:.`)

8.13 Marking math environments

A general mechanism for math mode environments that do not grab their content (*cf.* most `amsmath` environments).

`\l__math_env_name_tl` To allow us to carry out “special effects”

```

934 \tl_new:N \l__math_env_name_tl

```

Here we set up specialized handling of environments. The idea for the `arg-spec` key is that if an environment takes arguments, we don’t worry during the main grabbing. Rather, we remove the arguments from the grabbed content and forward only the payload. That is done by (ab)using `ltxcmd`.

```

935 \keys_define:nn { __math }
936 {
937   arg-spec .code:n =
938   {
939     \ExpandArgs { c } \DeclareDocumentCommand
940     { __math_env \l__math_env_name_tl _aux: }
941     {#1}
942     { \__math_env_forward:w }
943   }
944 }

```

`\math_register_env:nn` Set up to capture environment content and make available.
`\math_register_env:n`
`\RegisterMathEnvironment`

```

945 \cs_new_protected:Npn \math_register_env:nn #1#2
946 {

```

```

947 \tl_set:Nn \l__math_env_name_tl {#1}
948 \keys_set:nn { __math } {#2}
949 \cs_gset_eq:cc { __math_env_ #1 _begin: } {#1}
950 \cs_gset_eq:cc { __math_env_ #1 _end: } { end #1 }
951 %
952 \ExpandArgs { nnee } \RenewDocumentEnvironment {#1} { b }
953 {
954   \exp_not:N \bool_if:NTF \exp_not:N \l__math_collected_bool
955   {
956     \typeout{==>B1}
957   }
958   {
959     \typeout{==>B2}
960     \cs_if_exist:cTF { __math_env_ #1 _aux: }
961     {
962       \exp_not:c { __math_env_ #1 _aux: }
963       ##1 \exp_not:N \__math_env_end: {#1}
964     }
965     { \exp_not:N \__math_process:nn {#1} {##1} }
966     \exp_not:n { \@kernel@math@registered@begin }
967     \bool_set_true:N \exp_not:N \l__math_collected_bool
968   }
969   %
970   \exp_not:N \tracingall
971   \exp_not:c { __math_env_ #1 _begin: }
972   ##1
973   %
974   \exp_not:N \tracingnone
975 }
976 {
977   \exp_not:c { __math_env_ #1 _end: }
978 }
979 }

978 \cs_new:Npn \@kernel@math@registered@begin {
979 % \ShowTagging{struct-stack}
980 %\typeout{==>A1}\ShowTagging{struct-stack,mc-current}

Before we start math display processing we need to output a dangling run-in heading,
otherwise it gets inserted too late when tagging for the formula has already started.

981 \if@noskipsec \leavevmode \fi

982 \mode_if_vertical:TF
983 {
984   \__block_beginpar_vmode:
985 }
986 {
987   \UseTaggingSocket{para/textblock/end}
988 }
989 \tag_socket_use:nn{math/display/formula/begin}{-}{-}
990 % \typeout{==>MC1}\ShowTagging{mc-current}
991 }

992
993 \cs_new_protected:Npn \math_register_env:n #1
994 { \math_register_env:nn {#1} { } }
995
996 \NewDocumentCommand \RegisterMathEnvironment { O{} m }

```

```
997 { \math_register_env:nn {#2} {#1} }
```

(End of definition for `\math_register_env:nn`, `\math_register_env:n`, and `\RegisterMathEnvironment`. These functions are documented on page 5.)

```
\__math_env_forward:w
```

```
998 \cs_new_protected:Npn \__math_env_forward:w #1 \__math_env_end: #2
```

```
999 { \__math_process:nn {#2} {#1} }
```

(End of definition for `\__math_env_forward:w`.)

8.14 Regaining control after a display has finished with `$$`

The tagging structures have to be added after the formula content but before $\TeX$ is allowed to break a page. But $\TeX$ will automatically add `\postdisplaypenalty` followed by `\belowdisplayskip` or `\belowdisplayshortskip` without giving us any chance to take control before these are added.

We therefore implement the following approach:

- Just before we end the formula we save away the current value of `\postdisplaypenalty` in case it was altered within the formula. Then we set it to 10000 so that what is inserted by $\TeX$ is not allowing for a page break at this point
- At this point we also normally flip the sign of `\belowdisplayskip` and `\belowdisplayshortskip` so that they become negative and record that we have done this, by setting the token list `\g__math_skip_sign_tl` to `-`.
- However, we only do that if both are non-negative. If either of them is negative we assume that this was deliberately done by the user to adjust the spacing around this particular display. Again, we record in `\g__math_skip_sign_tl` that we haven't done the sign flip by setting the variable to empty.
- Making these two skips negative is essential, because the formula will be added using the special `\postdisplaypenalty` value that doesn't allow a page break even though the real value (that we use later on) will probably do that. Thus the below skip added by $\TeX$ will add to the size of the display and not vanish into the bottom margin and if it is positive $\TeX$ might decide to move the whole formula onto the next page even though it might well fit.
- Once $\TeX$ has finished processing the closing `$$` it has added something like

```
\penalty 100000          % our special value for \postdisplaypenalty
\glue -10.0 plus -3pt    % the \belowdisplayskip (with sign flipped
```

after the formula. This means that at this that point we can retrieve this skip by using `\lastskip` and we just have to flip the sign again to know how to correct it (no need to know whether the normal or the short skip was added by $\TeX$) and the right penalty is available to us too as we have saved it away in `\g__math_postdisplaypenalty_int`.

```
\__math_prepare_display_end:
```

Prepare to finish the formula and give control to $\TeX$. This is normally used directly in front of `$$` (`\eqno` or `\leqno`).

```
1000 \cs_new_protected:Npn \__math_prepare_display_end: {
```

```
1001   \bool_lazy_or:nnTF
```

```
1002     { \dim_compare_p:nNn \belowdisplayskip < {0pt} }
```

```
1003     { \dim_compare_p:nNn \belowdisplayshortskip < {0pt} }
```

No sign flipping if one or both of the skips are already negative.

```
1004 { \tl_gclear:N \g__math_skip_sign_tl }
```

Otherwise flip the sign of both.

```
1005 {
1006   \tl_gset:Nn \g__math_skip_sign_tl {-}
1007   \skip_set:Nn \belowdisplayskip {-\belowdisplayskip}
1008   \skip_set:Nn \belowdisplayshortskip {-\belowdisplayshortskip}
1009 }
```

For the skip it is enough to flip the sign, because we get the value back through `\lastskip` but for the `\postdisplaypenalty` change we have to save the current value somewhere, because it may have been changed within the display formula. This has to be done globally, because it is used after the formula has ended.

```
1010 \int_gset_eq:NN \g__math_postdisplaypenalty_int \postdisplaypenalty
1011 \int_set_eq:NN \postdisplaypenalty \@M
1012 }
```

(End of definition for `\__math_prepare_display_end:`)

`\__math_tag_dollardollar_display_end:`

The code to be executed after the formula has ended is injected using `\group_insert_after:N` inside of `\tex_everydisplay:D` (i.e., when the formula starts but inside the group started by the display). As `\group_insert_after:N` expects a single token we have to store that code in a command.

```
1013 \cs_new_protected:Npn \__math_tag_dollardollar_display_end:
1014 {
1015   % \typeout{== tag dollarldollar display end}
1016   % \ShowTagging{struct-stack}
1017   \para_raw_end:
```

The `\postdisplaypenalty` was temporarily set to 10000 inside the display and both the `\belowdisplayskip` and the `\belowdisplayshortskip` were negated (with some exceptions, see above), so whatever was inserted it should have been a negative or possibly zero skip. Whatever was added, we pick up the value, so that we can correct the spacing after the tagging code has been inserted.

```
1018 \l__math_tmpa_skip \lastskip
1019 \tag_socket_use:n{math/display/formula/end}
```

Now we add a skip without introducing a page break possibility, that should bring the current vertical position back to the point where $\text{\TeX}$ has added the penalty and the “below skip”.

```
1020 \nobreak
1021 \skip_vertical:n { -\l__math_tmpa_skip }
```

Then we finally add the real stuff: the true `\postdisplaypenalty` (saved in `\g__math_postdisplaypenalty_int` earlier) and the negated value of the skip value we saved in `\l__math_tmpa_skip`. It may look strange that we have two identical negated skips next to each other, but if you think about it, that is correct: the first cancels the “below skip” that $\text{\TeX}$ has added and the second puts the same amount of skip after the penalty (which is where it should be).

```
1022 \penalty \g__math_postdisplaypenalty_int
```

As we are now in vertical mode the situation is different from the way $\TeX$ would handle things after a display: $\TeX$ would internally switch to horizontal mode without adding a `\parskip`. But this is not possible to do on the macro level. Therefore we have to neutralize the upcoming `\parskip` since we can't prevent it from being added. We have to do this before re-adding the saved skip, because we want to make this skip seen by any following `\addvspace`. Otherwise, we might end up with too much space in such a situation. .

```
1023     \skip_vertical:n { -\tex_parskip:D }
1024     \skip_vertical:n
```

Actually, we use the skip without flipping the sign when our records show that it wasn't flipped earlier i.e., when the negative value was due to the user specifying it inside the formula.

```
1025     { \g__math_skip_sign_tl \l__math_tmpa_skip } }
```

We also set the `@domathendpetrue` flag to signal that paragraph continuation should happen after such a display.

```
1026     \@domathendpetrue
1027     \@doendpe           % this has no \end{...} to take care of it
1028 }
```

(End of definition for __math_tag_dollardollar_display_end:.)

`\g__math_postdisplaypenalty_int` This is the internal variable in which we save the `\postdisplaypenalty`. It is global because we use it immediately after the formula has ended.

```
1029 \int_new:N \g__math_postdisplaypenalty_int
```

(End of definition for \g__math_postdisplaypenalty_int.)

`\g__math_skip_sign_tl` We record whether we have flipped the signs of `\belowdisplayskip`, etc., so that we know what to do after the formula has ended. If we have it flipped the signs then variable holds `-`, whilst otherwise it is empty. This means we can flip the signs again by simply prefixing the value with this token list variable.

```
1030 \tl_new:N \g__math_skip_sign_tl
```

(End of definition for \g__math_skip_sign_tl.)

`\dollardollar@end` When we do tagging we augment the kernel definition for `\dollardollar@end` in order to regain control at the very end of the formula (after the user may have altered `\postdisplaypenalty` or `\belowdisplayskip`).

```
1031 \def \dollardollar@end { \__math_prepare_display_end: $$ }
```

(End of definition for \dollardollar@end.)

`\eqno` `\leqno` However, in case of a formula using the primitives `\eqno` or `\leqno` the `\dollardollar@end` comes too late as it is executed in the context of the equation number; and the values for `\postdisplaypenalty`, etc. set at this point are not the ones used for the formula. We therefore have to execute `\__math_prepare_display_end:` just in front of the primitive.

```
1032 \protected\def\eqno{
1033   \__math_prepare_display_end:
```

Inside the equation we set it temporarily to do nothing, because otherwise it would be executed again when `\dollar\dollar@end` is reached (not that this would matter, but it would just take unnecessary extra time).

```

1034 \kernel@eqno
1035 \cs_set_eq:NN \__math_prepare_display_end: \prg_do_nothing:
1036 \aftergroup\ignorespaces
1037 }

```

Same game for `\leqno`.

```

1038 \protected\def\leqno{
1039 \__math_prepare_display_end:
1040 \kernel@leqno
1041 \cs_set_eq:NN \__math_prepare_display_end: \prg_do_nothing:
1042 \aftergroup\ignorespaces
1043 }

```

(End of definition for `\eqno` and `\leqno`.)

8.15 Document commands

Add one more here: `displaymath`, which is equivalent to `\[ , \]` and hence to the basic `equation*`.
Added in more recent branch.

`\equation`

`\__math_equation_begin:`

`\equation*`

`\__math_equation_star_begin:`

`\endequation`

`\__math_equation_end:`

`\endequation*`

`\__math_equation_star_end:`

These environments are not set up by `amsmath` to collect their body, so we do that here. This has to be done *after* we can be sure `amsmath` is loaded. Note that with `amsmath` loaded, `equation*` and `equation` are the two basics: they are used to define the other single-row display environments, etc.

```

1044 \tl_gput_right:Nn \kernel@before@begindocument
1045 {
1046 \math_register_env:n { equation }
1047 \math_register_env:n { equation* }
1048 % at the moment register_env can only do display math
1049 % \math_register_env:n { math }
1050 \RenewDocumentEnvironment{math} {b}{\$#1\$}{}
1051 % and this one doesn't work either
1052 % \math_register_env:n { displaymath }
1053 \RenewDocumentEnvironment{displaymath} {b}{\[#1\]}{}
1054 }

```

(End of definition for `\equation` and others.)

- \(If math mode has not been collected, we need to do that; otherwise, worry about whether
- \) we are in math mode or not. The closing command here can only occur inside a collected math block: otherwise it will be simply used as a delimiter.

```

1055 \cs_gset_protected:Npn \(\ % \)
1056 {
1057 \bool_if:NTF \l__math_collected_bool
1058 {
1059 \mode_if_math:TF
1060 { \badmath }
1061 { $ }
1062 }

```

```

1063     {
1064       \__math_grab_inline:w
1065     }
1066   } % \(\
1067   \cs_gset_protected:Npn \)
1068   {
1069     \mode_if_math:TF
1070     { $ }
1071     { \@badmath }
1072   }

```

(End of definition for \(\ and \).)

\[Again, we need to watch for when `amsmath` is loaded after this code. The flag usage here
\] is to cover the case where `\[/\]` is hidden inside another environment. In this case the grabbing happens on the outer level and should not be repeated.

```

1073 \tl_gput_right:Nn \@kernel@before@begindocument
1074 {
1075   \cs_gset_protected:Npn \[ % \[
1076   {
1077     \__math_grab_eqn:w
1078   } % \[
1079   \cs_gset_protected:Npn \]
1080   {
1081     \@badmath
1082   }
1083 }

```

(End of definition for \[and \].)

8.16 \everymath and \everydisplay

The business end for grabbing inline math and “raw” $\TeX$ display. Most display math mode is actually handled elsewhere, as we have macro control.

```

1084 \exp_args:No \tex_everymath:D
1085 {
1086   \tex_the:D \tex_everymath:D
1087   \bool_if:NF \l__math_collected_bool
1088   {
1089     \bool_set_true:N \l__math_collected_bool
1090     \__math_grab_dollar:w
1091   }
1092 }
1093
1094 \exp_args:No \tex_everydisplay:D
1095 {
1096   \tex_the:D \tex_everydisplay:D
1097   % \typeout{==>~ in~ everydisplay}

```

We need to attach tagging after the display math has been processed by $\TeX$, and we also need to correct the penalty and spacing that will get added there. This is done by the following code through which we regain control after the display math group ends.

```

1098   \group_insert_after:N \__math_tag_dollardollar_display_end:
1099   \bool_if:NF \l__math_collected_bool

```

```

1100     {
1101       \bool_set_true:N \l__math_collected_bool
1102       \__math_grab_dollardollar:w
1103     }
1104   }

```

8.17 Modifying kernel environments

We need to cover this even though it is, of course, not encouraged. Registration is delayed until `begindocument` to avoid error with redefinition in, e.g., `fleqn.clo`.

```

1105 \tl_gput_right:Nn \@kernel@before@begindocument
1106 {
1107   \math_register_env:n { eqnarray }
1108   \math_register_env:n { eqnarray* }
1109 }

```

In `tabulars` we do need to change the grabbing method to the slow loop-method. `\@kernel@tabular@init` is provided in `array.sty` which is loaded by the table code.

```

1110 \providecommand\@kernel@tabular@init{}
1111 \tl_put_right:Nn\@kernel@tabular@init
1112 {
1113   \cs_set_protected:Npn \__math_grab_dollar:w { \__math_grab_loop_init: }
1114   \cs_set_protected:Npn \__math_grab_inline:w { $ }
1115 }

```

`\__math_m@th:` Handle non-math use of math mode. At present nesting isn't supported as `\m@th` pops up in a few places that *are* math mode!

```

1116 \cs_new_eq:NN \__math_m@th: \m@th
1117 \cs_gset_protected:Npn \m@th
1118 {
1119   \bool_set_true:N \l__math_collected_bool
1120   \__math_m@th:
1121 }

```

(End of definition for `\__math_m@th:` and `\m@th`.)

8.18 Modifying kernel commands

`\mathpalette` The `\mathpalette` command is a problem if `lualatex` is used and math structure elements are created as the math is then processed more than once. We therefore redefine it to use `\mathstyle`.

```

1122 \sys_if_engine luatex:T
1123 {
1124   \def\mathpalette#1#2{%
1125     \ifcase\mathstyle
1126       #1\displaystyle{#2}\or
1127       #1\displaystyle{#2}\or
1128       #1\textstyle{#2}\or
1129       #1\textstyle{#2}\or
1130       #1\scriptstyle{#2}\or
1131       #1\scriptstyle{#2}\or
1132       #1\scriptscriptstyle{#2}\or
1133       #1\scriptscriptstyle{#2}

```

```

1134   \fi}
1135 }

```

(End of definition for \mathpalette.)

\mathsm@sh Similar to the phantom commands in latex-lab-text, \mathsm@sh must be redefined to include luamml sockets.

```

1136 \def\mathsm@sh#1#2{%
1137   \setbox\z@\hbox{$\m@th#1#2}
1138   \UseTaggingSocket{math/luamml/save/nNn}{\mathsmash} #1 {mpadded}}
1139   $}%
1140   \UseTaggingSocket{math/luamml/finsm@sh}{\finsm@sh}}

```

(End of definition for \mathsm@sh.)

\eqnarray For MathML generation in eqnarray we also need to add some sockets.
\endeqnarray

```

1141 <@@=)
1142 \def\eqnarray{%
1143   \stepcounter{equation}%
1144   \def\@currentlabel{\p@equation\theequation}%
1145   \def\@currentcounter{equation}%
1146   \global\@eqnswtrue
1147   \m@th
1148   \global\@eqcnt\z@
1149   \tabskip\@centering
1150   \let\\\@eqncr
1151   \dollar\dollar@begin\everycr{}\halign to\displaywidth\bgroup
1152     \hskip\@centering
1153     $\displaystyle\tabskip\z@skip{##}%
1154     \UseTaggingSocket{math/luamml/save/nNn}{\displaystyle {mtd}}%
1155     $%
1156     \UseTaggingSocket{math/luamml/mtable/finalizecol}{last}%
1157     \@eqnset
1158     &\global\@eqcnt\@ne\hskip \tw@\arraycolsep \hfil${##}%
1159     \UseTaggingSocket{math/luamml/save/nNn}{\displaystyle {mtd}}%
1160     $%
1161     \UseTaggingSocket{math/luamml/mtable/finalizecol}{last}%
1162     \hfil
1163     &\global\@eqcnt\tw@ \hskip \tw@\arraycolsep $\displaystyle{##}%
1164     \UseTaggingSocket{math/luamml/save/nNn}{\displaystyle {mtd}}%
1165     $%
1166     \UseTaggingSocket{math/luamml/mtable/finalizecol}{last}%
1167     \hfil\tabskip\@centering
1168     &\global\@eqcnt\thr@@ \hb@xt@\z@\bgroup\hss##\egroup
1169     \UseTaggingSocket{math/luamml/mtable/tag/set}
1170     \tabskip\z@skip
1171   \cr
1172 }
1173 \def\endeqnarray{%
1174   \@eqncr
1175   \UseExpandableTaggingSocket{math/luamml/mtable/finalize} {eqnarray}%
1176   \egroup
1177   \global\advance\c@equation\@ne
1178   \dollar\dollar@end\@ignoretrue
1179 }

```

```

1180 \AddToHook{file/fleqn.clo/after}{
1181   \renewenvironment{eqnarray}{%
1182     \stepcounter{equation}%
1183     \def\@currentlabel{\p@equation\theequation}%
1184     \def\@currentcounter{equation}%
1185     \global\@eqnswtrue\m@th
1186     \global\@eqcnt\z@
1187     \tabskip\mathindent
1188     \let\=\@eqnocr
1189     \setlength\abovedisplayskip{\topsep}%
1190     \ifvmode
1191       \addtolength\abovedisplayskip{\partopsep}%
1192     \fi
1193     \addtolength\abovedisplayskip{\parskip}%
1194     \setlength\belowdisplayskip{\abovedisplayskip}%
1195     \setlength\belowdisplayshortskip{\abovedisplayskip}%
1196     \setlength\abovedisplayshortskip{\abovedisplayskip}%
1197     \dollar\dollar@begin\everycr{}\halign to\linewidth%
1198       \bgroup
1199       \hskip\@centering
1200       $\displaystyle\tabskip\z@skip{##}%
1201       \UseTaggingSocket{math/luamml/save/nNn}{\displaystyle {mtd}}%
1202       $%
1203       \UseTaggingSocket{math/luamml/mtable/finalizecol}{last}%
1204       \@eqnse1&%
1205       \global\@eqcnt\@ne \hskip \tw@\arraycolsep \hfil${##}%
1206       \UseTaggingSocket{math/luamml/save/nNn}{\displaystyle {mtd}}%
1207       $%
1208       \UseTaggingSocket{math/luamml/mtable/finalizecol}{last}%
1209       \hfil&%
1210       \global\@eqcnt\tw@ \hskip \tw@\arraycolsep $\displaystyle{##}%
1211       \UseTaggingSocket{math/luamml/save/nNn}{\displaystyle {mtd}}%
1212       $%
1213       \UseTaggingSocket{math/luamml/mtable/finalizecol}{last}%
1214       \hfil \tabskip\@centering&%
1215       \global\@eqcnt\thr@@
1216       \hb@xt@\z@\bgroup\hss##\egroup
1217       \UseTaggingSocket{math/luamml/mtable/tag/set}
1218       \tabskip\z@skip\cr
1219   }%
1220   {%
1221     \@@eqnocr
1222     \UseExpandableTaggingSocket{math/luamml/mtable/finalize} {eqnarray}%
1223     \egroup
1224     \global\advance\c@equation\m@ne
1225     \dollar\dollar@end
1226     \@ignoretrue
1227   }
1228 }
1229 \@@=math

```

(End of definition for \eqnarray and \endeqnarray.)

8.19 Disable math grabbing in the begindocument hook

For example amsart uses math to measure text there.

```

1230 \tl_gput_right:Nn\@kernel@before@begindocument
1231 {
1232   \bool_set_true:N\l__math_collected_bool
1233 }
1234 \tl_gput_right:Nn\@kernel@after@begindocument
1235 {
1236   \bool_set_false:N\l__math_collected_bool
1237 }

1238 \ExplSyntaxOff

1239 <@@= >

1240 </kernel>

```

Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

Symbols	
\#	97, 376
\%	98
\(	833
\(	1055
\)	834, 881
\)	1055
@@ commands:	
\l_@@_collected_bool	3, 12
\l_@@_content_template_tl	9
\l_@@_fakemath_bool	12
\[	843, 1053
\[	13, 36, 44, 45, 1073
\]	215, 216, 217, 218,
	219, 220, 282, 883, 887, 927, 1150, 1188
\{	95
\}	96
\]	844, 1053
\]	13, 36, 44, 45, 1073
\^	99
A	
\abovedisplayshortskip	1196
\abovedisplayskip	1189, 1191, 1193, 1194, 1195, 1196
actual+source (plug)	622
\AddToHook	8, 9, 163, 169, 175,
	191, 203, 254, 357, 397, 414, 441, 1180
\addtolength	1191, 1193
\addvspace	43
\advance	1177, 1224
\aftergroup	1036, 1042
alt+source (plug)	637
\arraycolsep	1158, 1163, 1205, 1210
\AssignTaggingSocketPlug	228, 229, 233, 355, 356,
	395, 396, 592, 593, 652, 693, 694,
	767, 768, 769, 770, 771, 772, 773, 774
B	
\begin	38, 598, 616, 847, 889, 894
\begingroup	94
\belowdisplayshortskip	41, 42, 1003, 1008, 1195
\belowdisplayskip	41–43, 1002, 1007, 1194
\bgroup	1151, 1168, 1198, 1216
block internal commands:	
_block_beginpar_vmode:	984
bool commands:	
\bool_gset_false:N	20, 322
\bool_gset_true:N	15, 227, 277, 318, 343, 384
\bool_if:NTF	26, 28, 73, 225, 265, 392, 451,
	659, 669, 681, 713, 718, 728, 735,
	743, 748, 846, 954, 1057, 1087, 1099
\bool_lazy_any:nTF	803
\bool_lazy_or:nnTF	186, 1001

<code>\bool_new:N</code>	10, 33, 34, 35, 47, 48, 49, 50, 51, 52, 53, 276
<code>\bool_set_false:N</code>	270, 310, 795, 840, 1236
<code>\bool_set_true:N</code> 268, 303, 455, 502, 781, 796, 967, 1089, 1101, 1119, 1232	
bool internal commands:	
<code>\l_math_collected_bool</code>	14, 33, 265, 268, 270, 795, 796, 840, 846, 954, 967, 1057, 1087, 1089, 1099, 1101, 1119, 1232, 1236
<code>\g_math_debug_bool</code>	14, 10, 15, 20, 26, 28
<code>\l_math_fakemath_bool</code> 15, 34, 781, 806	
<code>\g_math_luaaml_write_bool</code>	22, 225, 276, 277, 318, 322, 326
<code>\l_math_math_content_artifact_-bool</code>	15, 35, 303, 310, 681
box commands:	
<code>\box_clear:N</code>	391
<code>\box_new:N</code>	367
box internal commands:	
<code>\l_math_tmpa_box</code>	367, 370, 391
<code>\boxed</code>	12
C	
char commands:	
<code>\char_set_catcode_other:N</code>	95, 96, 97, 98, 99, 376
clist commands:	
<code>\clist_map_inline:Nn</code>	378
<code>\clist_map_inline:nn</code>	475
<code>\clist_new:N</code>	61
<code>\clist_put_right:Nn</code>	62, 491, 503
<code>\cr</code>	921, 1171, 1218
cs commands:	
<code>\cs_generate_variant:Nn</code> 427, 695, 785	
<code>\cs_gset_eq:NN</code>	949, 950
<code>\cs_gset_protected:Npe</code>	25, 27
<code>\cs_gset_protected:Npn</code>	1055, 1067, 1075, 1079, 1117
<code>\cs_if_exist:NTF</code>	960
<code>\cs_if_exist_p:N</code>	187, 188
<code>\cs_if_exist_use:N</code>	745, 750
<code>\cs_if_exist_use:NTF</code>	875
<code>\cs_if_free:NTF</code>	146, 151, 156
<code>\cs_new:Npn</code>	237, 278, 279, 978
<code>\cs_new_eq:NN</code>	11, 12, 79, 1116
<code>\cs_new_protected:Npe</code>	896
<code>\cs_new_protected:Npn</code>	13, 18, 23, 30, 31, 64, 80, 93, 102, 143, 223, 368, 418, 776, 786, 792, 793, 797, 798, 821, 823, 833, 842, 843, 851, 857, 866, 868, 873, 879, 881, 883, 889, 905, 915, 918, 929, 945, 993, 998, 1000, 1013
<code>\cs_set:Npn</code>	300, 301
<code>\cs_set_eq:NN</code>	148, 153, 158, 308, 309, 377, 501, 1035, 1041
<code>\cs_set_protected:Npn</code>	264, 794, 795, 796, 921, 1113, 1114
D	
<code>\DebugMathOff</code>	11, 30
<code>\DebugMathOn</code>	11, 30
<code>\DeclareDocumentCommand</code>	939
<code>\DeclareMathEnvironment</code>	13
<code>\def</code>	1031, 1032, 1038, 1124, 1136, 1142, 1144, 1145, 1173, 1183, 1184
default (plug)	526, 546, 557, 576, 655
dim commands:	
<code>\dim_compare_p:nNn</code>	1002, 1003
<code>\displaylines</code>	13
<code>\displaystyle</code>	1126, 1127, 1153, 1154, 1159, 1163, 1164, 1200, 1201, 1206, 1210, 1211
<code>\displaywidth</code>	1151
E	
<code>\egroup</code>	1168, 1176, 1216, 1223
<code>\end</code>	38, 602, 618, 847, 896, 901, 903, 905, 908, 1027
<code>\endeqnarray</code>	1141
<code>\endequation</code>	1044
<code>\endequation*</code>	1044
<code>\endgroup</code>	103
<code>\ensuremath</code>	13
<code>\equalign</code>	13
<code>\eqnarray</code>	1141
<code>\eqno</code>	41, 43, 1032
<code>\equation</code>	1044
<code>\equation*</code>	1044
<code>\everycr</code>	1151, 1197
<code>\everydisplay</code>	45
<code>\everymath</code>	3, 45
exp commands:	
<code>\exp_args:NNV</code>	931
<code>\exp_args:No</code>	1084, 1094
<code>\exp_last_unbraced:Ne</code>	446
<code>\exp_not:N</code>	598, 602, 616, 618, 898, 900, 901, 903, 954, 962, 963, 965, 967, 969, 970, 972, 975
<code>\exp_not:n</code>	600, 612, 617, 966
<code>\ExpandArgs</code>	939, 952
<code>\ExplSyntaxOff</code>	1238
<code>\ExplSyntaxOn</code>	7
F	
<code>\fi</code>	981, 1134, 1192

fi commands:		<code>\g__math_mathchoice_int</code> 25, 415
<code>\fi:</code> 920, 926		<code>\g__math_mathml_AF_attached_int</code>
file commands:		 16, 60, 409, 720
<code>\file_if_exist:nTF</code> 380		<code>\g__math_mathml_AF_found_int</code> . . .
<code>\file_input:n</code> 383		 16, 59, 407, 717
G		<code>\g__math_mathml_int</code> . . . 16, 57, 70, 403
<code>\GetDocumentProperty</code> 447		<code>\g__math_mathml_total_int</code>
<code>\global</code>		 16, 56, 67, 401
1146, 1148, 1158, 1163, 1168, 1177,		<code>\l__math_mathstyle_int</code> 415, 422
1185, 1186, 1205, 1210, 1215, 1224		<code>\g__math_mml_int</code> 16
group commands:		<code>\g__math_mml_total_int</code> 16
<code>\group_align_safe_begin:</code> . . . 800, 893		<code>\g__math_postdisplaypenalty_int</code>
<code>\group_align_safe_end:</code> 802, 910		 41, 42, 1010, 1022, 1029
<code>\group_begin:</code> 853		<code>\intertext</code> 13
<code>\c_group_begin_token</code> 861		iow commands:
<code>\group_end:</code> 931		<code>\iow_close:N</code> 258, 361
<code>\group_insert_after:N</code> 42, 1098		<code>\iow_new:N</code> 234, 346
H		<code>\iow_newline:</code>
<code>\halign</code> 1151, 1197		110, 112, 117, 119, 134, 136, 138, 140
<code>\hbox</code> 1137		<code>\iow_now:Nn</code> 236, 244, 256, 332, 351, 359
hbox commands:		<code>\iow_open:Nn</code> 235, 347
<code>\hbox_set:Nn</code> 370		<code>\iow_term:n</code>
<code>\hfil</code> . . . 1158, 1162, 1167, 1205, 1209, 1214		 399, 400, 401, 403, 405, 407, 409
<code>\hskip</code> . . 1152, 1158, 1163, 1199, 1205, 1210		iow internal commands:
<code>\hss</code> 1168, 1216		<code>\g__math_luamml_iow</code>
I		 234, 235, 236, 244, 256, 258
if commands:		<code>\g__math_writedummy_iow</code>
<code>\if_false:</code> 920, 926		 332, 344, 346, 347, 351, 359, 361
<code>\ifcase</code> 1125		K
<code>\ifvmode</code> 1190		keys commands:
<code>\ignorespaces</code> 913, 1036, 1042		<code>\keys_define:nn</code> 285, 339, 428, 458, 935
int commands:		<code>\keys_set:nn</code> 464, 477, 483, 493, 508, 948
<code>\int_compare:nNnTF</code>		L
. 241, 424, 885, 892, 898, 909		<code>\lastskip</code> 41, 42, 1018
<code>\int_decr:N</code> 271, 907		<code>\LaTeXe</code> 12
<code>\int_gincr:N</code> 67, 70, 702, 717, 720		<code>\leavevmode</code> 9, 981
<code>\int_gset_eq:NN</code> 1010		legacy commands:
<code>\int_incr:N</code> 891		<code>\legacy_if:nTF</code> 778
<code>\int_new:N</code> 56,		<code>\legacy_if_p:n</code> 805
57, 58, 59, 60, 415, 416, 850, 1029		<code>\leqno</code> 41, 43, 44, 1032
<code>\int_set:Nn</code> 230, 422		<code>\let</code> 1150, 1188
<code>\int_set_eq:NN</code> 1011		<code>\linewidth</code> 1197
<code>\int_use:N</code>		<code>\ltxlabmathdate</code> 3
. . . . 135, 401, 403, 405, 407, 409, 417		<code>\ltxlabmathversion</code> 4
int internal commands:		luamml commands:
<code>\g__math_AF_attached_int</code> 16		<code>\luamml_flag_ignore:</code> 155, 158
<code>\g__math_AF_found_int</code> 16		<code>\luamml_flag_process:</code> 150, 153
<code>\g__math_AF_total_int</code> 16		<code>\luamml_flag_structelem:</code> . . 145, 148
<code>\l__math_grab_env_int</code>		<code>\luamml_ignore:</code> . . . 156, 158, 301, 313
. . . 37, 850, 885, 891, 892, 898, 907, 909		<code>\luamml_process:</code> 151, 153
<code>\g__math_math_total_int</code>		<code>\luamml_structelem:</code> 146, 148, 300
. 16, 58, 135, 405, 702		

luamml internal commands:		
\l__luamml_pretty_int	230	
__luamml_register_output_hook:N	253	
M		
\m@th	3	
maketag internal commands:		
\maketag_math@	29	
math commands:		
\math_debug_off:	11, 13, 18, 31	
\math_debug_on:	11, 13, 13, 30	
\math_processor:n	5, 793, 793	
\math_register_env:n	5, 945,	993, 1046, 1047, 1049, 1052, 1107, 1108
\math_register_env:nn		5, 945, 945, 994, 997
math internal commands:		
__math_AF_html_reader:w	93, 377	
__math_AF_html_reader_verb:w		100, 102
__math_AF_mml:nnnn	64, 64, 104	
__math_AF_process_mathml_files:		367, 368, 414
__math_debug:n	11, 11, 25	
__math_debug_gset:	13, 16, 21, 23	
__math_debug_typeout:n		11, 12, 27, 680, 721, 724, 756
__math_env_end:	963, 998	
__math_env_forward:w	942, 998, 998	
__math_equation_begin:	1044	
__math_equation_end:	1044	
__math_equation_star_begin:	1044	
__math_equation_star_end:	1044	
__math_grab:n	797, 798, 822, 932	
__math_grab_dollar:w		797, 797, 1090, 1113
__math_grab_dollar_delim:w		797, 821, 821
__math_grab_dollardollar:w		823, 823, 1102
__math_grab_eqn:w	843, 843, 1077	
__math_grab_inline:w		842, 842, 1064, 1114
__math_grab_inline_delim:w		833, 833, 842
__math_grab_loop:		851, 855, 857, 871, 911, 916, 923
__math_grab_loop_\$:	873	
__math_grab_loop_\:	873	
__math_grab_loop_\begin:	873	
__math_grab_loop_\end:	873	
__math_grab_loop_\end:n	873	
__math_grab_loop_\ignorespaces:	873	
__math_grab_loop_\textonly@unskip:		873
__math_grab_loop_\unskip:	873	
__math_grab_loop_end:		880, 882, 929, 929
__math_grab_loop_group:n		862, 866, 866
__math_grab_loop_init:	851, 851, 1113	
__math_grab_loop_newline:		886, 900, 918, 918
__math_grab_loop_store:n		866, 867, 868, 877, 887, 894
__math_grab_loop_token:N		863, 873, 873
__math_luamml_activate_write:		22, 171, 193, 223
__math_luamml_ignore:		278, 279, 301, 309, 810
__math_luamml_output_hook:n	237, 253	
__math_luamml_structelem:		278, 278, 300, 308, 530, 562
__math_m@th:	1116, 1116, 1120	
__math_MSFT_mml:nn	79, 79, 105, 501	
__math_MSFT_mml_aux:nn	79, 80, 501	
__math_prepare_display_end:		43, 830, 1000,
__math_process:nn		1000, 1031, 1033, 1035, 1039, 1041
__math_process_auxi:nn	775, 776, 785, 801, 826, 965, 999	
__math_process_auxii:nn	775, 782, 786	
__math_process_auxiii:nn	775, 790, 792, 794	
__math_provide_luamml_commands:		143, 199, 205
__math_tag_dollardollar_		display_end: 1013, 1013, 1098
__math_tag_if_mathstyle:nn		418, 418, 427
math/content (tag socket)	621	
math/display/begin (tag socket)	542	
math/display/end (tag socket)	542	
math/display/formula/begin (tag socket)	542	
math/display/formula/end (tag socket)	542	
math/display/tag/begin (tag socket)	574	
math/display/tag/end (tag socket)	574	
math/end (tag socket)	766	
math/inline/begin (tag socket)	514	
math/inline/end (tag socket)	514	
math/inline/formula/begin (tag socket)	514	
math/inline/formula/end (tag socket)	514	
math/mathml/write (tag socket)	329	
math/mathml/write/prepare (tag socket)	125	
math/struct/begin (tag socket)	653	

str internal commands:		
\l__math_tmpa_str	15, 40, 128, 129, 130, 137	
\SuspendTagging	3	
\symletters	232	
\symsymbols	231	
sys commands:		
\sys_if_engine luatex:TF	161, 302, 1122	
\c_sys_jobname_str	63, 235, 349, 492, 504	
T		
\tabskip	1149, 1153, 1167, 1170, 1187, 1200, 1214, 1218	
tag commands:		
\tag_attr_new:nn	86	
\tag_if_active:TF	177	
\tag_mc_begin:n	582, 590, 683, 685, 757	
\tag_mc_begin_pop:n	525	
\tag_mc_end:	580, 588, 691, 763	
\tag_mc_end_push:	521	
\tag_resume:n	425	
\tag_socket_use:n	531, 532, 534, 540, 563, 564, 566, 572, 733, 734, 814, 817, 818, 827, 1019	
\tag_socket_use:nn	828, 989	
\tag_socket_use:nnn	815	
\tag_struct_begin:n	6, 581, 671, 738	
\tag_struct_end:	589, 691, 764	
\tag_suspend:n	425	
tag internal commands:		
\l__tag_math_alt_bool	16, 52, 431, 451, 455, 669, 713	
\g__tag_math_lua_mml_tl	16, 54, 55	
\g__tag_math_mathml_AF_bool	16, 50, 227, 343, 384, 392	
\l__tag_math_mathml_AF_bool	16, 49, 436, 718, 728, 748	
\l__tag_math_mathml_files_clist	16, 61, 62, 378, 430, 491, 503	
\l__tag_math_mathml_pane_bool	16, 51, 73, 433	
\l__tag_math_MSFT_bool	16, 53, 432, 502, 743	
\l__tag_math_texsource_AF_bool	16, 47, 438, 659, 735	
\l__tag_math_texsource_pane_bool	16, 48, 435	
Tagging Sockets:		
math/content	621	
math/display/begin	542	
math/display/end	542	
math/display/formula/begin	542	
math/display/formula/end	542	
math/display/tag/begin	574	
math/display/tag/end	574	
math/end	766	
math/inline/begin	514	
math/inline/end	514	
math/inline/formula/begin	514	
math/inline/formula/end	514	
math/mathml/write	329	
math/mathml/write/prepare	125	
math/struct/begin	653	
math/struct/end	653	
\tagpdfparaOff	529, 561	
\tagpdfsetup	219, 221	
TeX and L ^A T _E X 2 _ε commands:		
\@eqnocr	1174, 1221	
\@M	1011	
\@badmath	1060, 1071, 1081	
\@centering	1149, 1152, 1167, 1199, 1214	
\@currentcounter	1145, 1184	
\@currentlabel	1144, 1183	
\@doendpe	1027	
\@domathendpetrue	1026	
\@eqcnt	1148, 1158, 1163, 1168, 1186, 1205, 1210, 1215	
\@eqnocr	1150, 1188	
\@eqnsql	1157, 1204	
\@eqnswtrue	1146, 1185	
\@ignoretrue	1178, 1226	
\@iiiparbox	12	
\@kernel@after@begindocument	1234	
\@kernel@before@begindocument	1044, 1073, 1105, 1230	
\@kernel@eqno	1034	
\@kernel@leqno	1040	
\@kernel@math@registered@begin	966, 978	
\@kernel@tabular@init	46, 1110, 1111	
\@math@level	242, 271	
\@ne	1158, 1205	
\c@equation	1177, 1224	
\cr	37–39	
\dollardollar@begin	1151, 1197	
\dollardollar@end	43, 44, 1031, 1178, 1225	
\finism@sh	1140	
\frozen@everymath	21	
\halign	35, 38	
\hb@xt@	1168, 1216	
\if@noskipsec	981	
\ifmeasuring@	5, 12, 775	
\m@ne	1177, 1224	
\m@th	4, 12, 13, 15, 36, 46, 780, 1116, 1137, 1147, 1185	

use commands:		<code>\UseTaggingSocket</code>	
<code>\use_i:nn</code>	446	.	550, 987, 1138, 1140, 1154, 1156,
<code>\use_none:n</code>	11, 12		1159, 1161, 1164, 1166, 1169, 1201,
<code>\use_none:nn</code>	79		1203, 1206, 1208, 1211, 1213, 1217
<code>\UseExpandableTaggingSocket</code> .	1175, 1222		
<code>\UseMathForPositioningText</code>	21, 264	V	
<code>\UseStructureName</code>	581, 673, 740	<code>\vcenter</code>	3, 12, 21